

### Main

Product or component type	Connector
Accessory / separate part category	Connection accessory
Product compatibility	Plug Easy56 EY56P310
Plug, socket category	Low voltage
Poles description	1P + N + E
Pin number	3 pins
Shape of pin	Flat
Network type	AC
Outlet standard	Australian/New Zealand

### Complementary

Plug, socket, control station shape	Straight
[In] rated current	10 A
[Ue] rated operational voltage	250 V
Network frequency	50 Hz
Material	Polycarbonate housing :
Contacts material	Brass sleeves :
Connections - terminals	Screw terminals
Cable cross section	0.75...1 mm <sup>2</sup>
Wire stripping length	12...34 mm
Cable outer diameter	6.8...10.6 mm
Cable entry	Cable gland
Thread type	M20
Product weight	0.107 kg
Height	65 mm
Width	65 mm
Depth	105 mm
Colour	Clear body ) Orange ( RAL 2004 ) plug )
Targeted country	Australia New Zealand
Market segment	Utility Industry Small commercial

### Environment

Standards	AS/NZS 3120
Quality labels	RCM
IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-25...75 °C
Ambient air temperature for storage	-25...75 °C

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.