



Main

| | |
|-------------------------------|--|
| Range of product | Harmony Control Relays |
| Product or component type | 3-phase control relay |
| Relay type | Control relay |
| Network number of phases | 3 phases |
| Relay name | RM22TA |
| Relay monitored parameters | Phase sequence Phase failure detection Asymmetry |
| Time delay type | Adjustable 0.1...30 s, +/- 10 % of the full scale value on crossing the threshold Tt |
| Switching capacity in VA | 2000 VA |
| Measurement range | 380...480 V voltage AC |
| Contacts type and composition | 2 C/O |

Complementary

| | |
|---|---|
| Reset time | 1500 Ms at maximum voltage |
| Maximum switching voltage | 250 V AC |
| Minimum switching current | 10 MA at 5 V DC |
| Maximum switching current | 8 A AC |
| [Us] rated supply voltage | 380...480 V AC |
| Supply voltage limits | 304...576 V AC |
| Control circuit voltage limits | - 20 % + 20 % Un |
| Power consumption in VA | 15 VA at 480 V AC 60 Hz |
| Voltage detection threshold | < 100 V AC |
| Supply frequency | 50...60 Hz +/- 10 % |
| Output contacts | 2 C/O |
| Setting accuracy of the switching threshold | +/- 10 % of the full scale |
| Switching threshold drift | <= 0.05 % per degree centigrade depending permissible ambient air temperature <= 1 % within the supply voltage range |
| Setting accuracy of time delay | 10 P |
| Time delay drift | <= 0.05 % per degree centigrade depending permissible ambient air temperature <= 1 % within the supply voltage range |
| Hysteresis | 2 % fixed of selectable |
| Run-up delay at power-up | 650 Ms |
| Maximum measuring cycle | 150 Ms measurement cycle as true rms value |
| Threshold adjustment voltage | 2...20 % of Un selected |
| Voltage range | 380...480 V phase to phase |

| | |
|-----------------------------------|--|
| Adjustment of asymmetry threshold | 5...15 % of Un selected |
| Repeat accuracy | +/- 0.5 % for input and measurement circuit +/- 3 % for time delay |
| Measurement error | < 1 % over the whole range with voltage variation < 0.05 %/°C with temperature variation |
| Response time | <= 300 ms |
| Overvoltage category | III conforming to IEC 60664-1 III conforming to UL 508 |
| Insulation resistance | > 100 MOhm at 500 V DC conforming to IEC 60255-27 |
| Mounting position | Any position |
| Connections - terminals | Screw terminals, 2 x 0.5...2 x 2.5 mm ² (AWG 20...AWG 14) solid without cable end Screw terminals, 2 x 0.2...2 x 1.5 mm ² (AWG 24...AWG 16) flexible with cable end Screw terminals, 1 x 0.5...1 x 3.3 mm ² (AWG 20...AWG 12) solid without cable end Screw terminals, 1 x 0.2...1 x 2.5 mm ² (AWG 24...AWG 14) flexible with cable end |
| Tightening torque | 0.6...1 N.M conforming to IEC 60947-1 |
| Housing material | Self-extinguishing plastic |
| Status LED | LED (yellow)relay ON LED (green)power ON |
| Mounting support | 35 mm DIN rail conforming to EN/IEC 60715 |
| Electrical durability | 100000 Cycles |
| Mechanical durability | 10000000 Cycles |
| Utilisation category | AC-15 conforming to IEC 60947-5-1 DC-13 conforming to IEC 60947-5-1 AC-1 conforming to IEC 60947-4-1 DC-1 conforming to IEC 60947-4-1 |
| Safety reliability data | MTTFd = 388.1 years B10d = 350000 |
| Contacts material | Cadmium free |
| Width | 22.5 Mm |
| Net weight | 0.09 Kg |

Environment

| | |
|-------------------------------------|--|
| Immunity to microbreaks | 10 Ms |
| Electromagnetic compatibility | Immunity for residential, commercial and light-industrial environments conforming to EN/IEC 61000-6-1 Immunity for industrial environments conforming to EN/IEC 61000-6-2 Emission standard for residential, commercial and light-industrial environments conforming to EN/IEC 61000-6-3 Emission standard for industrial environments conforming to EN/IEC 61000-6-4 Electrostatic discharge - test level: 6 kV level 3 (contact discharge) conforming to IEC 61000-4-2 Electrostatic discharge - test level: 8 kV level 3 (air discharge) conforming to IEC 61000-4-2 Radiated radio-frequency electromagnetic field immunity test - test level: 10 V/m level 3 conforming to IEC 61000-4-3 Electrical fast transient/burst immunity test - test level: 4 kV level 4 (direct) conforming to IEC 61000-4-4 Electrical fast transient/burst immunity test - test level: 2 kV level 4 (capacitive-coupling) conforming to IEC 61000-4-4 Surge immunity test - test level: 4 kV level 4 (common mode) conforming to IEC 61000-4-5 Surge immunity test - test level: 2 kV level 4 (differential mode) conforming to IEC 61000-4-5 Conducted and radiated emissions class B group 1 conforming to CISPR 11 Conducted and radiated emissions class B conforming to CISPR 22 |
| Standards | EN/IEC 60255-1 |
| Product certifications | GL EAC CCC CE CSA UL RCM |
| Ambient air temperature for storage | -40...70 °C |

| | |
|---------------------------------------|--|
| Ambient air temperature for operation | -20...50 °C at 60 Hz -20...60 °C at 50 Hz AC/DC |
| Relative humidity | 93...97 % at 25...55 °C conforming to IEC 60068-2-30 |
| Vibration resistance | 0.075 mm (f= 10...58.1 Hz) not in operation conforming to IEC 60068-2-6 1 gn (f= 10...58.1 Hz) not in operation conforming to IEC 60068-2-6 0.035 mm (f= 58.1...150 Hz) in operation conforming to IEC 60068-2-6 0.5 gn (f= 58.1...150 Hz) in operation conforming to IEC 60068-2-6 |
| Shock resistance | 15 gn (duration = 11 ms) for not in operation conforming to IEC 60068-2-27 5 gn (duration = 11 ms) for in operation conforming to IEC 60068-2-27 |
| IP degree of protection | IP20 (terminals) conforming to IEC 60529 IP40 (housing) conforming to IEC 60529 IP50 (front panel) conforming to IEC 60529 |
| Pollution degree | 3 conforming to IEC 60664-1 3 conforming to UL 508 |
| Dielectric test voltage | 2.5 KV, 1 min AC 50 Hz conforming to IEC 60255-27 |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 104 G |
| Package 1 Height | 2.6 Cm |
| Package 1 width | 8.2 Cm |
| Package 1 Length | 9.5 Cm |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Product Life Status : **Commercialised**