

# Product data sheet

## Characteristics

# LV429424

## trip unit accessory - SDTAM 24/415V AC/DC - for NSX100..250 / NSX400..630



### Main

|                                |  |
|--------------------------------|--|
| Commercial Status              | Commercialised   |
| Range of product               | NSX100...250<br>NSX400...630   |
| Device short name              | SDTAM  |
| Accessory / separate part type | Trip unit accessories  |
| Trip unit name                 | Micrologic 2.2-M<br>Micrologic 2.3-M<br>Micrologic 6.2 E-M<br>Micrologic 6.3 E-M |

### Complementary

|                           |                                |
|---------------------------|--------------------------------|
| [In] rated current        | $\leq 0.08$ A                  |
| [Us] rated supply voltage | 24...415 V DC<br>24...415 V AC |

### Offer Sustainability

|                          |   |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product   |
| RoHS                     | Compliant - since 0818 - <a href="#">Schneider Electric declaration of conformity</a> |

### RoHS compliance

|                                |           |
|--------------------------------|-----------|
| RoHS EUR status                | Compliant |
| RoHS EUR conformity date(YYWW) | 0818      |

### Contractual warranty

|        |           |
|--------|-----------|
| Period | 18 months |
|--------|-----------|