

# Product datasheet

Specifications



## Earth-leakage add-on protection module VigiPacT, ComPacT NSX 100/160, 200VAC to 440VAC, 30mA to 30A, 3 poles

LV429488

### Main

<b>Range of product</b>	ComPacT NSX100...250 new generation ComPact NSX100...250
<b>Device short name</b>	VigiPacT
<b>product or component type</b>	Vigi add-on
<b>Device application</b>	Wiring
<b>Range compatibility</b>	ComPacT new generation ComPacT NSX100 new generation circuit breaker ComPacT new generation ComPacT NSX160 new generation circuit breaker ComPact ComPact NSX100 circuit breaker ComPact ComPact NSX160 circuit breaker
<b>poles description</b>	3P
<b>[In] rated current</b>	100 A 160 A
<b>Earth-leakage protection class</b>	Class A Class AC
<b>Residual earth-leakage sensitivity adjustment type</b>	Adjustable
<b>Earth-leakage sensitivity</b>	0.03 A for class A 0.1 A for class A 0.3 A for class A 0.5 A for class A 1 A for class A 3 A for class A 10 A for class AC 30 A for class AC
<b>Residual earth-leakage time delay adjustment type</b>	Adjustable
<b>[<math>\Delta</math>] residual earth-leakage time delay adjustment</b>	0 ms 60 ms 150 ms 300 ms 500 ms 800 ms 1.2 s 4 s

### Complementary

<b>Network type</b>	AC
<b>Network frequency</b>	50/60 Hz
<b>[Ue] rated operational voltage</b>	200...440 V AC 50/60 Hz conforming to IEC 60947-2
<b>Earth-leakage protection</b>	With
<b>Maximum breaking time</b>	800 ms
<b>Overvoltage category</b>	IV

## Environment

---

Electrical shock protection class	Class II
-----------------------------------	----------

---

Standards	IEC 60947-2
-----------	-------------

---

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	13.000 cm
------------------	-----------

---

Package 1 Width	14.500 cm
-----------------	-----------

---

Package 1 Length	17.000 cm
------------------	-----------

---

Package 1 Weight	1.093 kg
------------------	----------

---

Unit Type of Package 2	S04
------------------------	-----

---

Number of Units in Package 2	12
------------------------------	----

---

Package 2 Height	30.000 cm
------------------	-----------

---

Package 2 Width	40.000 cm
-----------------	-----------

---

Package 2 Length	60.000 cm
------------------	-----------

---

Package 2 Weight	13.735 kg
------------------	-----------

---

Unit Type of Package 3	P12
------------------------	-----

---

Number of Units in Package 3	48
------------------------------	----

---

Package 3 Height	42.000 cm
------------------	-----------

---

Package 3 Width	80.000 cm
-----------------	-----------

---

Package 3 Length	120.000 cm
------------------	------------

---

Package 3 Weight	67.200 kg
------------------	-----------

---

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

## Well-being performance

Mercury Free

Rohs Exemption Information Yes

## Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)  
Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)