

Product data sheet

Characteristics

NSYPLAZ12104G

Floor standing encl.polyester vers.PLAZ w/plinth
open bottom 1250x1000x420 IP54



Main

Range	Thalassa
Product name	Thalassa PLA
Device application	Multi-purpose
Product or component type	Suitable enclosure
Device short name	PLAZ
Enclosure nominal height	1250 mm
Enclosure nominal width	1000 mm
Enclosure nominal depth	420 mm
Enclosure mounting	Floor-standing
Device composition	1 top part 1 bottom part 2 rear panel 2 door 1 plinth 2 side part

Complementary


Body type	Sealed top and open bottom part assembled with side parts
Door type	Plain front
Number of doors	2
Door opening	Right and left 120 °
Lock type	4 points lock, handle with 5 mm double bar insert
Accessibility for operation	Front Rear Bottom
Removable parts	Door by hinges Rear panel by fixing element
Material	Polyester reinforced with fibreglass
Colour	Grey RAL 7035
Standards	IEC 62208

Product certifications	Veritas
------------------------	---------

Environment

IP degree of protection	IP54 plinth type open bottom IEC 60529
IK degree of protection	IK10 plain door IEC 62262
Fire resistance	960 °C IEC 62208
Ambient air temperature for storage	-35...90 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity