Product data sheet Characteristics

NSYPLS2754G

PLS box, polyester rear, transparent PC cover IP65 27x54x18cm



Main

	80	
Main		
Range	Thalassa	
Product name	Thalassa PLS	
Device short name	PLS	
Device application	Multi-purpose	
Product or component type	Insulating modular box	
Enclosure nominal height	270 mm	
Enclosure nominal width	540 mm	
Enclosure nominal depth	180 mm	
Enclosure mounting	Wall mounted	
Device composition	Cover 1 on enclosure	
	Locking screws	
	Rear part 1 on enclosure	
Body type	One piece moulded	
Type of front cover	Low transparent cover	
Lock type	Slot screw	
Complementary		
Removable parts	Cover locking screw	
Material	Polycarbonate cover Polyester reinforced with fibreglass rear	
Colour	Grey RAL 7035 body	
Standards	NEMA 4X IEC 62208 NEMA classification 13	
Product certifications	UL	
Environment		
Electrical insulation class	Class II	
May 16, 2017		

Complementary

Removable parts	Cover locking screw	
Material	Polycarbonate cover Polyester reinforced with fibreglass rear	
Colour	Grey RAL 7035 body	
Standards	NEMA 4X IEC 62208 NEMA classification 13	
Product certifications	UL	

Environment

Electrical in	sulation class
---------------	----------------

May 16, 2017

IP degree of protection	IP65 IEC 60529
IK degree of protection	IK09 IEC 62262
Fire resistance	960 °C IEC 62208
Ambient air temperature for storage	-3070 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 1511 - Schneider Electric declaration of conformity
	🛃 Schneider Electric declaration of conformity