



## Main

Range	Spacial S3X
Enclosure type	Multi-purpose
Category	Compact enclosure
Nominal height	1000 mm
Nominal width	1000 mm
Nominal depth	300 mm
Product installation	Wall-mounting
Device composition	1 reinforcement frame drilled ( door ) 1 lock ( door ) 2 door 1 body

## Complementary

Body type	Gutter shaped front rail Single piece body, cross-shaped structure
Door type	Plain
Number of doors	Front face : 2 door(s)
Door opening	120 °, reversible
Lock type	3 points lock, 3 mm double-bar
Mounting plate description	Without mounting plate
Type of gland plate	Without gland plate
Accessibility for operation	Front
Removable parts	Door fixing: by hinges
Material	Body and door : stainless steel 316L Hinge : stainless steel
Surface finish	Body and door : Scotch-Brite® brushed
Thickness	1.5 mm

## Environment

Standards	IEC 62208
Product certifications	CAN/CSA 22 UL 508 type A
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Environmental characteristic	Corrosive Specific hygiene

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0940 - <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations