



Main

| | |
|---------------------|---|
| Range | Thalassa TBS |
| Device application | Multi-purpose |
| Category | Industrial box |
| Height | 116 mm |
| Width | 74 mm |
| Depth | 62 mm |
| Internal height | 105 mm |
| Internal width | 65 mm |
| Internal depth | 55 mm |
| Enclosure mounting | Wall mounted |
| Device composition | 4 x cover screw 1 x cover 1 x body |
| Quantity per set | Set of 5 |
| Body type | One piece moulded |
| Type of front cover | Low plain cover |
| Cover fixing | Metal screws |
| Lock type | Outside sealed area: flat screwdriver captive screw |
| Removable parts | Cover, by captive screws |

Complementary

| | |
|-------------------------------------|------------------------------------|
| Material | ABS |
| Colour | Grey (RAL 7035) |
| Standards | IEC 62208 |
| Product certifications | DEMKO SEMKO TÜV |
| IP degree of protection | IP66conforming to NEMA 4.4X |
| IK degree of protection | IK07conforming to IEC 62262 |
| Fire resistance | 650 °Cconforming to IEC 60695-2-11 |
| Ambient air temperature for storage | -15...40 °C |
| Operating temperature | -25...60 °C |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS | Compliant - since 0940 - Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |

Contractual warranty

| | |
|--------|-----------|
| Period | 18 months |
|--------|-----------|