



Main

Range of product	Harmony XALF Harmony XB5
Product or component type	Head for illuminated selector switch
Device short name	ZB5
Bezel material	Plastic
Mounting diameter	22 mm
Sale per indivisible quantity	1
IP degree of protection	IP69 K IEC 60529
Shape of signaling unit head	Round
Type of operator	Stay put
Operator profile	Standard handle green
Operator position information	2 positions 90°

Complementary

Product weight	0,016 kg
Resistance to high pressure washer	7000000 Pa 55 °C 0.1 m
Mechanical durability	500000 cycles

Environment

Protective treatment	TH
Ambient air temperature for storage	-40...70 °C
Ambient air temperature for operation	-25...70 °C
Class of protection against electric shock	Class II IEC 60536
NEMA degree of protection	NEMA 13 NEMA 4X
IK degree of protection	IK06 IEC 50102
Standards	CSA C22-2 No 14 EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 JIS C 4520 UL 508
Product certifications	BV CSA DNV (Det Norske Veritas) GL LROS RINA UL listed
Vibration resistance	5 gn 2...500 Hz IEC 60068-2-6
Shock resistance	30 gn 18 ms half sine wave acceleration IEC 60068-2-27 50 gn 11 ms half sine wave acceleration IEC 60068-2-27
RoHS EUR conformity date	0636
RoHS EUR status	Compliant