

Commercial Gateway

SE1000-CCG-G-S1



All-in-one communication gateway

- Wireless connections including optional WiFi, Zigbee and GSM modules
- Environmental sensors support
- Power reduction interface
- Electricity meter reader
- Non-SolarEdge inverter data loggers
- Easy installation DIN rail and wall mount



POWER				
Power Supply - Wall Mount	Included, 100-240VAC	Included, 100-240VAC, EU/UK/US/AU interchangeable, 2-pin plug		
Supply Voltage		9-14		
Connector Type	terminal block			
Power Consumption	<2			W
ANALOG SENSOR INPUT				
Number of Inputs	3			
	Range	Accuracy	Resolution	
Input 1	0-30mV or 0-2V	+/- 1% f.s		
Input 2	0-2V or 0-10V		10 bit	
Input 3	-20mA – 20mA			
COMMUNICATION INTERFACES				
Ethernet Interface		10/100-BaseT		
Wireless Connections	Wi	WiFi or ZigBee modules (*)		
GSM Module Interface	2G/3G GSM*			
Power Reduction Interface	4 control pins, 5V, GND			
RS485 Interface	2 ports; May be used for local connection			
SUPPORTED RS485 DEVICES (a)				
SolarEdge Devices		Yes		
Export Inverter Data		Yes		
Revenue meters		Yes		
Export Data to Non-SolarEdge Logger	Yes			
ENVIRONMENTAL				
Operating Temperatures		-20 to 60 / -4 to 140		
Protection Rating	IP20 Indoor			
MECHANICAL				
Mounting Type		DIN Rail / Wall mount		
Dimensions (LxWxH)	165 X 9	165 X 90.5 X 53.5 / 6.5 X 3.56 X 2.11		
Weight		0.5 / 1.1		
STANDARD COMPLIANCE				
Safety	U	UL60950-1, IEC-60950-1		
EMC	FCC Part 15 c	FCC Part 15 class B, IEC61000-6-2, IEC61000-6-3		

 $⁽a) for supported protocols and devices, see \\ link \\ \underline{http://www.solaredge.com/files/pdfs/se-gateway-supported-devices.pdf}$


^(*) sold separately - see individual product specs for supported locations



CONNECTION SCENARIOS

Example 1

Extend the Distance of Wired Connection



Example 2

Non-SolarEdge Logger & SolarEdge Monitoring **Parallel Connection**



Example 3

ZigBee Wireless Server Connection





