

Catalogue No: CA9-400-EI-11-480W

CONTACTOR 220kW 3P 250-500V AC/DC EI COIL 1NO 1NC AUX

Motor Control and Drives > Motor Starting and Protection > Contactors > Sprecher + Schuh Contactors > CA9
Contactors 55 to 630kW > 3 Pole Contactors with AC/DC Coil and PLC Interface



Representative Photo Only
(actual product may vary based on configuration selections)

- Simplifies selection with electronic wide-range AC/DC coils
- Available integrated PLC interface
- Saves energy with low power consumption
- Includes built-in surge suppression

SPECIFICATIONS

Product Series	CA9-400
Component Type Motor Control and Drives	Standard Contactor
Ie, Rated Operational Current, AC-1, 690V, 40°C	600 A@690V,40°C
Ie, Rated Operational Current, AC-1, 1kV, 40°C	600 A@1kV,40°C
kW Rating, AC-3, 415V, 60°C	220 kW @415V, 60°C
Ie, Rated Operational Current, AC-3, 415V, 60°C	400 A@415V,60°C
kW Rating, AC-3, 690V, 60°C	315 kW @690V, 60°C
Ie, Rated Operational Current, AC-3, 690V, 60°C	350 A@690V,60°C
kW Rating, AC-3, 1kV, 60°C	220 kW @1kV, 60°C
Ie, Rated Operational Current, AC-3, 1000V, 60°C	155 A@1000V,60°C
Coil Type	Electronic w/ PLC Interface type

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-