Catalogue No: D7P-LMM45

PUSHBUTTON 22.5mm PLASTIC MUSH MOM 40mm ILLUM YELLOW

Operator Control Devices > Pushbuttons and Control Switches > Pushbuttons and Pilot Lights > Sprecher + Schuh D7 Pushbuttons and Pilot Lights > D7 Momentary Mushroom Head Pushbuttons > Plastic Body, Illuminated





Button mushroom plastic illuminated Yellow 40mm

- D7 pilot devices offer maximum flexibility and a wide choice for all 22.5mm operator applications with all type (e-stops, selector switches, pushbuttons, pilot lights and more), colour and contact configurations.
- Aesthetically appealing and modularly designed to make assembly and interchangeability easy.
- Operators exhibit low profile and stylish appearance while maintaining the rugged performance necessary for demanding environments
- D7P is a plastic operator with a captive black plastic front bezel.
 Constructed of high-grade thermoplastics, the D7P is suitable for almost all environments and strong chemical resistance.
- D7M has a die-cast zinc housing and mounting ring for rugged durability. Finished with corrosion resistant chrome plating, the D7M also features a captive shiny metal bezel for a polished appearance.

Representative Photo Only (actual product may vary based on configuration selections)

SPECIFICATIONS	
Component Type Pushbutton and Pilot Lights	Pushbutton
Operator Type	Pushbutton, Mushroom, Illuminated
Operator Action	Momentary
Diameter, Operator	40 mm
Colour, Operator	Yellow Colour
Material, Operator	Plastic
Operator Insert Type	Yellow insert
Material, Bezel	Glass-Filled Nylon / PA6 / PA66 (Polyamide 6)
Coupling Plate Included	No
Diameter, Mounting Hole	22.5 mm
Contact Block Included	No
Illuminated	Yes
Lamp Module Included	No
Tightening Torque, Nominal	1.7 Nm
Electrical Service Life at Un, In	500000 cycles
Mechanical service life	10000000 cycles
RoHS Approved	Yes
CE Marked	Yes
Operating Temperature, Max	70 °C max
Operating Temperature, min	-25 °C min
Storage Temperature, max	85 °C max
Storage Temperature, min	-25 °C min
Relative humidity, min	50 %RH
Relative humidity, max	95 %RH
IP Rating	IP66 IP65
Shock Acceleration (Max.)	100 g



Catalogue No: D7P-LMM45

PUSHBUTTON 22.5mm PLASTIC MUSH MOM 40mm ILLUM YELLOW





Shock Duration (Max.)	11 ms	
Vibration Acceleration (Max.)	10 g	
Vibration Displacement (Peak to Peak	Max.) 1.52 mm	
Vibration Frequency, Operational (Max	c.) 2000 Hz	
Vibration Duration (Max.)	180 min	
Standards Compliance	NEMA ICS-5 UL 508 EN 60947-1 EN 60947-5-1 EN 60947-5-5 EN 418	
Certifications	UL UR CSA CCC CE	
Shipping Approvals	RINA (Registro Italiano Navale) ABS (American Bureau of Shipping) Lloyd's Register of Shipping	
REFERENCES		
IECEx Certificate -		
Supplier Declaration of Conformity:		
Installation Guide: -		
User Manual: -		
Manufacturer Datasheet: Series	atasheet: Series D7_Manufacturer Datasheet	
Manufacturer Catalogue & Product Selection:		

