



Representative Photo Only
(actual product may vary based on configuration selections)

Terminal Through Double Deck 4mm² Grey

- Designed for ease of wiring, secure connections and durability
- Comprehensive range, offering a wide array of terminal types for most circuits and functions
- Terminals accommodate a full range of wire sizes from 0.5 to 70mm² wire cross section
- Cone shaped guide allows easy wire insertion
- Specialty terminals including two-level, grounding, diode, isolating, fuse, sensor and thermocouple terminals
- International approvals, UL recognized, IEC and CSA certified.

SPECIFICATIONS

Component Type Termination Wiring	Terminal
Number of Levels	2
Package Quantity	50 qty
Colour, Body / Housing	Grey colour
Wire / Conductor Size (Min)	0.5 mm ²
Wire / Conductor Size (Max)	4 mm ²
Wire Strip Length	9 mm
Tightening Torque, Nominal	0.6 Nm
In, Rated Current	32 A
Un, Nominal Voltage	500 V
Height	48.6 mm
Width	64 mm
Depth	6 mm
Insulation Temperature (Min)	-40 °C
Insulation Temperature (Max)	90 °C

Catalogue No: **V7-WD4**

SCREW TERMINAL 4mm 2 CONDUCTOR 32A GREY

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Terminals - Screw > Sprecher + Schuh Screw
Type Terminals V7-W > Double deck terminals > 4 mm²



REFERENCES

IECEX Certificate -

Supplier Declaration of
Conformity: -

Installation Guide: -

User Manual: -

Manufacturer Datasheet: -

Manufacturer Catalogue
& Product Selection: [V7WD4_Manufacturer Catalogue](#)