

Stanilite®

Economy exit LED - slide connect



Range

Economy range

Product group

Exit LED




Features



- Emergency classification
- LED technology 75,000 hours lamp life
- High temperature rated Lithium iron phosphate battery
- Slide connect bracket that provides strength and enables quick and easy maintenance
- IP20 rating
- Large terminal block (16mm²) for easy wiring
- Designed for direct replacement of installed economy exit LED EELED
- Includes all pictograph diffuser options
- Universal wall/ceiling mounting, can also be rod or wire suspended

Catalogue no.	Description
Standard products	
ECOEXIT1BOX	Economy exit LED pictograph
Spare parts	
03-01228	Battery LiFePO4 6.4V 1.5Ah



Dimensions			
	Length	Width	Height (incl. bracket)
	362mm	100mm	224mm
Weight			
	Model	Weight	
	Standard	2.0kg	
Construction			
	Part	Construction	
	Body and diffuser	UV polycarbonate	
	Bracket	UV polycarbonate	

Light source			
	Model	Light source	
	Standard	Multiple LED strip	

Power consumption			
	Model	Power consumption	
	Standard	6.5W	

Note: Preliminary results

Photometrics			
	Model	Class	Classification
	Standard	C0	D2.5
		C90	E2.5

Note: Preliminary results

Note:

- Designed to comply with AS2293 and meet relevant Australian EMC standards