

# SYLED

## FEATURES

- Up to 88Lm/W
- Dimmable on standard Leading/Trailing edge systems
- IP20 classification (IP54 on request)
- High Power Factor 0.95
- Simple installation
- ?Average Life: 40,000 hr
- Product Warranty: 4 years\*

## KEY APPLICATIONS

- Building Vicinity
- Facade
- Retail
- LED Technology




## LUMINAIRE CONSTRUCTION

## OPTIONS AVAILABLE

| Order Code | Description            | Dimensions  | Weight |
|------------|------------------------|-------------|--------|
| 700130     | Oyster LED 25W 5K IP20 | L390 X D102 | 0      |
| 700120     | Oyster LED 25W 3K IP20 | L390 X D102 | 0      |
| 700110     | Oyster LED 18W 5K IP20 | L360 X D93  | 0      |
| 700100     | Oyster LED 18W 3K IP20 | L360 X D93  | 0      |
| 700090     | Oyster LED 14W 5K IP20 | L306 X D68  | 0      |
| 700080     | Oyster LED 14W 3K IP20 | L306 X D68  | 0      |

Note: \* Based on maximum 10 hours usage per day



|              | 14W    | 18W   | 25W   |
|--------------|--------|-------|-------|
| Diameter (D) | 306 mm | 360mm | 390mm |
| Height (H)   | 68mm   | 93mm  | 102mm |

For more information,  
scan the QR code:

