

TemBreak 2 Thermal magnetic type MCCB L250NJ



200 kA

Current rating: 160 – 250 A

Interrupting capacity:

	Voltage	I _{cu}	I _{cs}
AC use	380/415	200	150
DC use	250V	40	40

Trip unit:

Adjustable thermal (0.63 I_r to 100% I_r) and adjustable magnetic (6 I_m to 10 I_m)

Dimensions (mm)

Poles	3	4
H	165	165
W	105	140
D (less toggle)	103	103
Toggle cut-out	48	
	105 (on chassis)	

L250NJ 3 Pole

Ampere

Rating	Adj. I _r ¹⁾	Adj. I _m ¹⁾	Cat. No.
NRC	Min - Max.	Min - Max.	
250	160 - 250	1500 - 2500	L250 NJ 3 250

L250NJ 4 Pole

Ampere

Rating	Adj. I _r ¹⁾	Adj. I _m ¹⁾	Cat. No.
NRC	Min - Max.	Min - Max.	
250	160 - 250	1500 - 2500	L250 NJ 4 250

Cross reference table

Section

Accessories	4
Application data	12
Characteristic curves	5
OCR / Trip unit set-up	5
Motor starting	12
Selectivity & Cascade	12
Chassis	6
Dimensions and mounting	5

Base standards

IEC 60947-2
AS/NZS 60947-2
EN 60947-2
JIS C 8201-2-1 Ann. 1
CE Mark

Approvals

ASTA (UK,AUS)
Marine
Lloyd's / UK
ABS / USA
GL / Germany
BV / France
NK / Japan
DNV / Norway

Notes: ¹⁾ Adj. I_r: Adjustable thermal setting
Adj. I_m: Adjustable magnetic setting
NRC: Nominal rated current
Magnetic only MCCBs available on request.

Replaces: TL225B

Note: Check exact ratings or dimensions to suit your application requirement