

# Catalogue No: **S160NN3**

## T2 MCCB NON AUTO 3P 160A

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 250 AF > Non-Auto Switch Disconnecter 250 AF



Representative Photo Only  
(actual product may vary based on configuration selections)

### T2 MCCB NON AUTO 160A 3P

- Wide range of fault interruption ratings from 25 to 200kA to cater for a wide spectrum of applications
- MCCB sizes available from 16 to 1600A with various common frames and common accessories
- Customer fit accessories available to enable quick and easy configuration
- Basic or Advanced trip units such AC/DC thermal magnetic, AC electronic, metering and communications types are available

#### SPECIFICATIONS

Component Type MCCB	Switch Disconnecter (Non-auto)
In, Rated Current at 45°C	160 A @45°C
Icm, Rated Short Circuit Making Capacity	6 kA Peak
Icw, Short Time Withstand Current, 300ms (rms)	3 kA, 300ms
Un, Nominal Operational Voltage, AC	690 V AC
Frame Size	250 AF size
Number of Poles	3
Ui, Rated Insulation Voltage	800 V (rms)
Height	165 mm
Width	105 mm
Depth	68 mm
Weight	1.5 kg
Standard Installation Method	Front Connection
Reverse Connection Of Supply Possible	Yes
Electrical Service Life at Un, In	20000 cycles
Mechanical service life	30000 cycles
Trip Unit Protection Type	Non-auto Switch Disconnecter
Standards Compliance	IEC 60947-2 AS/NZS 60947-2
Certifications	CE

Catalogue No: **S160NN3**  
**T2 MCCB NON AUTO 3P 160A**

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 250 AF > Non-Auto Switch Disconnecter 250 AF



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Technical Diagram