



Representative Photo Only
(actual product may vary based on configuration selections)

T2 MCCB NON AUTO 400A 3P

- Wide range of fault interruption ratings from 25 to 200kA to cater for a wide spectrum of applications
- MCCB sizes available from 16 to 1600A with various common frames and common accessories
- Customer fit accessories available to enable quick and easy configuration
- Basic or Advanced trip units such AC/DC thermal magnetic, AC electronic, metering and communications types are available

SPECIFICATIONS

Component Type MCCB	Switch Disconnecter (Non-auto)
In, Rated Current at 45°C	400 A @45°C
Icm, Rated Short Circuit Making Capacity	9 kA Peak
Icw, Short Time Withstand Current, 300ms (rms)	5 kA, 300ms
Un, Nominal Operational Voltage, AC	690 V AC
Frame Size	400 AF size
Number of Poles	3
Ui, Rated Insulation Voltage	800 V (rms)
Height	260 mm
Width	140 mm
Depth	103 mm
Weight	4.2 kg
Standard Installation Method	Front Connection
Electrical Service Life at Un, In	4500 cycles
Mechanical service life	15000 cycles
Trip Unit Protection Type	Non-auto Switch Disconnecter
Standards Compliance	IEC 60947-1 IEC 60947-3 AS/NZS 3947.3 AS/NZS 3947.2 IEC 60947-2
Certifications	CE

Catalogue No: **S400NN3**
T2 MCCB NON AUTO 3P 400A

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 400/630 AF > Non-Auto Switch Disconnecter 630 AF



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Technical Diagram