

Catalogue No: **T2SH00A20TA**

T2 SHUNT TRIP 240V AC

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 Internal Accessories 125 AF - 1600 AF > Shunt Trips T2SH



Representative Photo Only
(actual product may vary based on configuration selections)

T2 SHUNT TRIP 240V AC

- Customers can fit - saves time.
- Wide range of internal accessories: Auxiliaries, Alarm contacts, Shunts Trip, Under Voltage Trips
- Common accessory range from 125AF to 1600AF, except for UVTs 800-1600A.
- Very low, standard and heavy duty (amp rating) auxiliaries and alarms - suits a variety of applications.
- Positive drive contact type auxiliaries and alarms (heavy duty type) - reflects the MCCBs main contact status.
- Cage terminal connection standard. Wire lead option for Auxiliaries and Alarms

SPECIFICATIONS

Details, compatible product series	Accessory common for MCCBs 125 A to 630 A; Wire lead types available
Component Type MCCB	Shunt Trip / Close
Ue, Rated Operational Voltage, AC, min	230 V AC
Ue, Rated Operational Voltage, AC, max	240 V AC
Coil Excitation Current, 200-480V AC	0.014 A
Compatible Frame Size	125 AF Compat.
Colour, Body / Housing	Grey colour
Wire / Conductor Size (Min)	0.5 mm ²
Wire / Conductor Size (Max)	1.25 mm ²

REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Catalogue No: **T2SH00A20TA**

T2 SHUNT TRIP 240V AC

Power Distribution and Protection > Circuit Breakers > Moulded Case Circuit Breakers > Terasaki TemBreak 2 Moulded Case Circuit Breakers > TemBreak 2 Internal Accessories 125 AF - 1600 AF > Shunt Trips T2SH

