




MINILED XDC10

10.5 Watts / 1390 Lumens / 90+ CRI



10 Watt LED downlight featuring a single COB LED design available in 2700K, 3000K, 4000K and 5000K colour temperature options in 90+ CRI or 2700K, 3000K and 4000K VIVID options. The Miniled range is supplied with remote driver.



System Power 11.7W

Tilt-Angle 30°

LED Power 10.5W

Cut-Out 92mm

IP Rating IP20

Weight 315g

	2700K	3000K	4000K	5000K	VIVID	2700K	3000K	4000K
COB Lumen Output	1300 lm	1335 lm	1390 lm	1410 lm	VIVID	1080 lm	1120 lm	1150 lm
Total Luminous Flux	1025 lm	1052 lm	1096 lm	1112 lm		851 lm	883 lm	906 lm

Efficacy	93.68 lm/W 4000K Wide Beam	Lifetime	50,000hrs (L80)		
Dimming	Leading + Trailing Edge	Optional: Dali 1-10v			
Input Voltage	100V - 240V AC 50/60 Hz	Protection	Thermal and Short Circuit	Power Factor	> 0.95

Product	CCT	Light Source	Beam Angle	Trim Colour	Driver
XDC10	2700K 2.7	90+ CRI	Wide Beam WB	White W	Leading + Trailing
	3000K 3	VIVID* V	Medium Beam MB	Black B	DALI*
	4000K 4		Narrow Beam NB	Silver S	1-10v*
	5000K 5				
XDC10	3		NB	W	

XDC103-NB-W

* Optional



TREND
LIGHT BY SOLID STATE

288 Coward Street, Mascot, NSW, 2020

Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au