




MINILED XDS15

15 Watts / 1960 Lumens / 90+ CRI



Fixed 15W downlight featuring a single COB LED. Available in 2700K, 3000K, 4000K and 5000K colour temperature options in 90+ CRI or 2700K, 3000K and 4000K VIVID options. Sealed face with silicone gasket for increased ingress protection and large passive heatsink for effective thermal management ensuring high output and long lifespan. Supplied with remote driver.



System Power	18.2W	Cut-Out	115mm
LED Power	15W	Weight	370g
IP Rating	IP44		

	2700K	3000K	4000K	5000K	VIVID	2700K	3000K	4000K
COB Lumen Output	1850 lm	1895 lm	1960 lm	1985 lm	VIVID	1585 lm	1635 lm	1670 lm
Total Luminous Flux	1558 lm	1608 lm	1636 lm	1688 lm		1298 lm	1343 lm	1383 lm

Efficacy	89.89 lm/W 4000K Wide Beam	Lifetime	50,000hrs (L80)
Dimming	Optional: Leading + Trailing Edge Dali 1-10v		
Input Voltage	100V - 240V AC 50/60 Hz	Protection	Thermal and Short Circuit
		Power Factor	> 0.95

Product	CCT	Light Source	Beam Angle	Trim Colour	Driver
XDS15	2700K 2.7	90+ CRI	Wide Beam WB	White W	Leading + Trailing* L&T
	3000K 3	VIVID* V	Medium Beam MB	Black B	DALI* DALI
	4000K 4		Narrow Beam NB	Silver S	1-10v* 1-10
	5000K 5				
XDS15	3		WB	W	

XDS153-WB-W

* Optional



TREND
LIGHT BY SOLID STATE

Level 3, 290-292 Coward Street, Mascot, NSW, 2020
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au