


PRODUCT CATALOGUE

IMPACT SOCKETS



1/2" STANDARD LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72008	8	15	25	6	38	110	
72009	9	16	25	6	38	110	
72010	10	17	25	6	38	153	
72011	11	18	25	8	38	170	
72012	12	19	25	8	38	203	
72013	13	21	25	8	38	249	
72014	14	22	25	8	38	282	
72015	15	23	30	9	38	339	TYRR50095
72016	16	24	30	9	38	407	TYRR50095
72017	17	26	30	9	38	475	TYRR50095
72018	18	27	30	9	38	542	TYRR50095
72019	19	28	30	10	38	565	TYRR50095
72020	20	30	30	12	38	570	TYRR50095
72021	21	30	30	12	38	570	TYRR50095
72022	22	32	30	12	38	570	TYRR50095
72023	23	32	30	14	40	570	TYRR50095
72024	24	34	30	14	40	570	TYRR50095
72025	25	36	30	14	40	570	TYRR50095
72026	26	36	30	14	43	570	TYRR50095
72027	27	38	30	14	43	570	TYRR50095
72028	28	40	30	16	43	570	TYRR50095
72029	29	40	30	16	43	570	TYRR50095
72030	30	42	30	16	43	570	TYRR50095
72032	32	44	30	18	43	570	TYRR50095
72033	33	45	30	20	46	570	TYRR50095
72034	34	46	30	20	46	570	TYRR50095
72035	35	48	30	20	50	570	TYRR50095
72036	36	50	30	20	50	570	TYRR50095
72038	38	52	30	20	50	570	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1/2" STANDARD LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72058	5/16	14	25	9	38	124	
72059	3/8	17	25	9	38	169	
72060	7/16	18.5	25	9	38	226	
72061	1/2	20.5	25	9	38	294	
72062	9/16	23	25	11	38	373	
72063	5/8	24.5	30	11	38	463	TYRR50095
72064	11/16	27	30	11	38	565	TYRR50095
72065	3/4	28	30	11	38	565	TYRR50095
72066	13/16	30	30	11	38	565	TYRR50095
72067	7/8	31.8	30	13	38	565	TYRR50095
72068	15/16	33.8	30	13	38	565	TYRR50095
72069	1	35.8	30	13	40	565	TYRR50095
72070	1-1/16	37.8	30	13	43	565	TYRR50095
72071	1-1/8	39.8	30	16.5	43	565	TYRR50095
72072	1-3/16	41.8	30	16.5	43	565	TYRR50095
72073	1-1/4	43.8	30	16.5	43	565	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1/2" DEEP LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72108	8	14	25	11	80	110	
72109	9	16.6	25	11	80	110	
72110	10	17	25	11	80	153	
72111	11	18.5	25	11	80	170	
72112	12	20	25	11	80	203	
72113	13	21	25	11	80	249	
72114	14	22.4	25	11	80	282	
72115	15	23	30	11	80	339	TYRR50095
72116	16	25	30	11	80	407	TYRR50095
72117	17	26	30	11	80	475	TYRR50095
72118	18	27.5	30	11	80	542	TYRR50095
72119	19	28.5	30	13	80	565	TYRR50095
72120	20	30	30	13	80	570	TYRR50095
72121	21	31.9	30	13	80	570	TYRR50095
72122	22	31.8	30	13	80	570	TYRR50095
72123	23	31.8	30	13	80	570	TYRR50095
72124	24	34.8	30	15	80	570	TYRR50095
72125	25	35.8	30	15	80	570	TYRR50095
72126	26	35.8	30	15	80	570	TYRR50095
72127	27	37.8	30	18.3	80	570	TYRR50095
72128	28	39.8	30	18.3	80	570	TYRR50095
72129	29	41.8	30	18.3	80	570	TYRR50095
72130	30	42	30	18.3	80	570	TYRR50095
72132	32	44	30	18.3	80	570	TYRR50095
72133	33	44.8	30	20	80	570	TYRR50095
72134	34	45.8	30	20	80	570	TYRR50095
72135	35	47.8	30	20	80	570	TYRR50095
72136	36	49.8	30	20	80	570	TYRR50095
72138	38	51.8	30	20	80	570	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1/2" DEEP LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72158	5/16	14	25	10	78	124	
72159	3/8	17	25	14	78	169	
72160	7/16	18.5	25	14	78	226	
72161	1/2	20.5	25	14	78	294	
72162	9/16	23	25	14	78	373	
72163	5/8	24.5	30	14	78	463	TYRR50095
72164	11/16	27	30	17	78	565	TYRR50095
72165	3/4	28	30	17	78	565	TYRR50095
72166	13/16	29.8	30	17	78	565	TYRR50095
72167	7/8	31.8	30	19	78	565	TYRR50095
72168	15/16	33.8	30	19	78	565	TYRR50095
72169	1	35.8	30	19	78	565	TYRR50095
72170	1-1/16	37.8	30	19	78	565	TYRR50095
72171	1-1/8	39.8	30	19	78	565	TYRR50095
72172	1-3/16	41.8	30	19	78	565	TYRR50095
72173	1-1/4	43.8	30	30	78	565	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

3/4" STANDARD LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72217	17	30	44	13	51	554	TY10032CG
72218	18	31	44	13	51	610	TY10032CG
72219	19	32.5	44	13	51	780	TY10032CG
72220	20	33.5	44	13	51	780	TY10032CG
72221	21	35	44	13	51	930	TY10032CG
72222	22	36	44	13	51	972	TY10032CG
72223	23	37.5	44	13	51	1015	TY10032CG
72224	24	38.5	44	16	51	1085	TY10032CG
72225	25	40	44	16	53	1160	TY10032CG
72226	26	41	44	16	53	1240	TY10032CG
72227	27	42.5	44	16	53	1580	TY10032CG
72228	28	44	44	19	53	1695	TY10032CG
72229	29	45	44	19	53	1810	TY10032CG
72230	30	46	44	19	53	1885	TY10032CG
72231	31	47.5	44	19	57	1955	TY10032CG
72232	32	48.5	44	19	57	2030	TY10032CG
72233	33	50	44	22	57	2030	TY10032CG
72234	34	51	44	22	57	2030	TY10032CG
72235	35	52.5	44	22	57	2030	TY10032CG
72236	36	53.5	44	22	57	2030	TY10032CG
72237	37	55	44	22	57	2030	TY10032CG
72238	38	56	44	22	57	2030	TY10032CG
72239	39	57	44	22	58	2030	TY10032CG
72240	40	58.5	44	22	58	2030	TY10032CG
72241	41	60	44	22	58	2030	TY10032CG
72242	42	61	44	25	58	2030	TY10032CG
72243	43	62.5	44	25	62	2030	TY10032CG
72244	44	64	44	25	62	2030	TY10032CG
72245	45	65	44	25	62	2030	TY10032CG
72246	46	66	44	25	62	2030	TY10032CG
72247	47	67	44	30	68	2030	TY10032CG
72248	48	68	44	30	68	2030	TY10032CG
72249	49	70	44	30	68	2030	TY10032CG
72250	50	71	44	30	68	2030	TY10032CG
72254	54	76	54	32	71	2200	TY18708CG
72255	55	78	54	32	71	2200	TY18708CG
72258	58	81	54	32	71	2200	TY18708CG
72260	60	83.5	54	34	73	2200	TY18708CG
72263	63	86	54	34	73	2200	TY18708CG
72265	65	88	54	34	73	2200	TY18708CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

3/4" STANDARD LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72275	1/2	23	41.4	13	51	418	TY10032CG
72276	9/16	25.5	41.4	13	51	418	TY10032CG
72277	5/8	28	41.4	13	51	497	TY10032CG
72278	11/16	29.5	41.4	13	51	576	TY10032CG
72279	3/4	32	41.4	13	51	780	TY10032CG
72280	13/16	35	41.4	13	51	926	TY10032CG
72281	7/8	36	41.4	13	51	972	TY10032CG
72282	15/16	38.5	41.4	13	51	1085	TY10032CG
72283	1	40	41.4	13	53	1243	TY10032CG
72284	1-1/16	42.5	44	13	53	1582	TY10032CG
72285	1-1/8	44	44	16	53	1808	TY10032CG
72286	1-3/16	46	44	16	53	1921	TY10032CG
72287	1-1/4	48	44	16	57	2034	TY10032CG
72288	1-5/16	50	44	19	57	2034	TY10032CG
72289	1-3/8	52.5	44	19	57	2034	TY10032CG
72290	1-7/16	53.5	44	19	57	2034	TY10032CG
72291	1-1/2	56	44	22	57	2034	TY10032CG
72292	1-9/16	58.5	44	22	58	2034	TY10032CG
72293	1-5/8	60	44	22	58	2034	TY10032CG
72294	1-11/16	63.5	44	26	62	2034	TY10032CG
72295	1-3/4	64.5	44	26	62	2034	TY10032CG
72296	1-13/16	66	44	26	62	2034	TY10032CG
72297	1-7/8	68	44	27	68	2034	TY10032CG
72298	1-15/16	70	44	27	68	2034	TY10032CG
72299	2	71	44	27	68	2034	TY10032CG
72300	2-1/16	74	54	31	71	2034	TY18708CG
72301	2-1/8	76	54	31	71	2034	TY18708CG
72302	2-3/16	78	54	31	71	2034	TY18708CG
72303	2-1/4	80	54	33	73	2034	TY18708CG
72304	2-5/16	81.5	54	33	73	2034	TY18708CG
72305	2-3/8	83.5	54	34	73	2034	TY18708CG
72306	2-7/16	85	54	34	75	2034	TY18708CG
72307	2-1/2	86.5	54	34	75	2034	TY18708CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

3/4" DEEP LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72317	17	30	44	19	90	554	TY10032CG
72318	18	31	44	19	90	610	TY10032CG
72319	19	32.5	44	19	90	780	TY10032CG
72320	20	33.5	44	19	90	780	TY10032CG
72321	21	35	44	19	90	930	TY10032CG
72322	22	36	44	19	90	972	TY10032CG
72323	23	37.5	44	19	90	1015	TY10032CG
72324	24	38.5	44	19	90	1085	TY10032CG
72325	25	40	44	19	90	1160	TY10032CG
72326	26	41	44	22	90	1240	TY10032CG
72327	27	42.5	44	22	90	1580	TY10032CG
72328	28	44	44	22	90	1695	TY10032CG
72329	29	45	44	22	90	1810	TY10032CG
72330	30	46	44	22	90	1885	TY10032CG
72331	31	47.5	44	22	90	1955	TY10032CG
72332	32	48.5	44	22	90	2030	TY10032CG
72333	33	50	44	25	90	2030	TY10032CG
72334	34	51	44	25	90	2030	TY10032CG
72335	35	52.5	44	25	90	2030	TY10032CG
72336	36	53.5	44	25	90	2030	TY10032CG
72337	37	55	44	25	90	2030	TY10032CG
72338	38	56	44	25	90	2030	TY10032CG
72339	39	57	44	25	90	2030	TY10032CG
72340	40	58.5	44	30	90	2030	TY10032CG
72341	41	60	44	30	90	2030	TY10032CG
72342	42	61	44	30	90	2030	TY10032CG
72343	43	62.5	44	30	90	2030	TY10032CG
72344	44	64	44	30	90	2030	TY10032CG
72345	45	65	44	30	90	2030	TY10032CG
72346	46	66	44	30	90	2030	TY10032CG
72347	47	67	44	30	90	2030	TY10032CG
72348	48	68	44	30	90	2030	TY10032CG
72349	49	70	44	30	90	2030	TY10032CG
72350	50	71	44	30	90	2030	TY10032CG
72354	54	76	54	40	100	2030	TY18708CG
72355	55	78	54	40	100	2030	TY18708CG
72358	58	81	54	40	100	2030	TY18708CG
72360	60	83.5	54	44	105	2030	TY18708CG
72363	63	86	54	44	105	2030	TY18708CG
72365	65	88	54	44	105	2030	TY18708CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

3/4" DEEP LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72375	1/2	23	41.4	16	90	418	TY10032CG
72376	9/16	25.5	41.4	16	90	418	TY10032CG
72377	5/8	28	41.4	16	90	497	TY10032CG
72378	11/16	29.5	41.4	16	90	576	TY10032CG
72379	3/4	32	41.4	16	90	780	TY10032CG
72380	13/16	35	41.4	16	90	926	TY10032CG
72381	7/8	36	41.4	16	90	972	TY10032CG
72382	15/16	38.5	41.4	16	90	1085	TY10032CG
72383	1	40	41.4	16	90	1243	TY10032CG
72384	1-1/16	42.5	44	16	90	1582	TY10032CG
72385	1-1/8	44	44	16	90	1808	TY10032CG
72386	1-3/16	46	44	16	90	1921	TY10032CG
72387	1-1/4	48.5	44	16	90	2034	TY10032CG
72388	1-5/16	50	44	22	90	2034	TY10032CG
72389	1-3/8	52.5	44	22	90	2034	TY10032CG
72390	1-7/16	53.5	44	22	90	2034	TY10032CG
72391	1-1/2	56	44	22	90	2034	TY10032CG
72392	1-9/16	58.5	44	22	90	2034	TY10032CG
72393	1-5/8	60	44	22	90	2034	TY10032CG
72394	1-11/16	63.5	44	27	90	2034	TY10032CG
72395	1-3/4	64.5	44	27	90	2034	TY10032CG
72396	1-13/16	66	44	27	90	2034	TY10032CG
72397	1-7/8	68	44	27	90	2034	TY10032CG
72398	1-15/16	70	44	27	90	2034	TY10032CG
72399	2	71	44	27	90	2034	TY10032CG
72400	2-1/16	74	54	31	100	2034	TY18708CG
72401	2-1/8	76	54	31	100	2034	TY18708CG
72402	2-3/16	78	54	31	100	2034	TY18708CG
72403	2-1/4	80	54	34	100	2034	TY18708CG
72404	2-5/16	81.5	54	34	105	2034	TY18708CG
72405	2-3/8	83.5	54	34	105	2034	TY18708CG
72406	2-7/16	85	54	34	105	2034	TY18708CG
72407	2-1/2	86	54	34	105	2034	TY18708CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" STANDARD LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72619	19	35	54	16	58	900	TY10008CG
72620	20	36	54	17	58	900	TY10008CG
72621	21	37.5	54	17	58	900	TY10008CG
72622	22	39	54	17	58	1240	TY10008CG
72623	23	40	54	17	58	1240	TY10008CG
72624	24	41.5	54	17	58	1470	TY10008CG
72625	25	42.5	54	17	60	1470	TY10008CG
72626	26	44	54	17	60	1470	TY10008CG
72627	27	45	54	17	60	1695	TY10008CG
72628	28	46.5	54	17	60	1955	TY10008CG
72629	29	47.5	54	19	62	1955	TY10008CG
72630	30	49	54	19	62	2225	TY10008CG
72631	31	50	54	19	62	2225	TY10008CG
72632	32	51.5	54	19	63	2490	TY10008CG
72633	33	52.5	54	21	63	2490	TY10008CG
72634	34	54	54	21	90	2490	TY10008CG
72635	35	55	54	21	66	2490	TY10008CG
72636	36	56.5	54	23	66	2712	TY10008CG
72637	37	58	54	23	66	2712	TY10008CG
72638	38	59	54	23	66	2712	TY10008CG
72639	39	60	54	23	66	2712	TY10008CG
72640	40	61	54	23	66	2712	TY10008CG
72641	41	62.5	54	25	68	2940	TY10008CG
72642	42	64	54	25	68	2940	TY10008CG
72643	43	65	54	25	70	2940	TY10008CG
72644	44	66	60.3	25	70	2940	TY10008CG
72645	45	67.5	60.3	25	70	2940	TY10008CG
72646	46	69	60.3	29	72	3390	TY10008CG
72647	47	70	60.3	29	72	3390	TY10008CG
72648	48	71.5	60.3	29	76	3390	TY10008CG
72649	49	73	60.3	29	76	3390	TY10008CG
72650	50	74	60.3	31	76	3615	TY10008CG
72651	51	75	60.3	31	76	3615	TY10010CG
72652	52	76.5	60.3	31	80	3615	TY10010CG
72653	53	78	60.3	31	80	3615	TY10010CG
72654	54	79	60.3	31	80	3615	TY10010CG
72655	55	80	60.3	34	84	3615	TY10010CG
72656	56	81.5	60.3	34	84	3615	TY10010CG
72657	57	82.5	60.3	34	84	3615	TY10010CG
72658	58	84	60.3	34	84	3615	TY10010CG
72659	59	85	60.3	34	88	3615	TY10010CG
72660	60	86.5	60.3	35	88	3615	TY10010CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" STANDARD LENGTH IMPACT SOCKETS, CR-MO METRIC CONTINUED



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72662	62	88	60.3	35	88	3615	TY10010CG
72663	63	90	60.3	35	88	3615	TY10010CG
72665	65	92.5	60.3	35	92	3615	TY10010CG
72667	67	95	60.3	35	92	3615	TY10010CG
72668	68	98	60.3	35	96	3615	TY10010CG
72669	69	98	60.3	35	96	3615	TY10010CG
72670	70	99	60.3	35	96	3615	TY10010CG
72671	71	100	60.3	35	96	3615	TY10010CG
72675	75	105	60.3	35	102	3615	TY10010CG
72677	77	108	60.3	35	102	3615	TY10021CG
72680	80	111.5	60.3	35	102	3615	TY10021CG
72685	85	117.5	86	35	106	3615	TY10021CG
72690	90	124	86	35	108	3615	TY10021CG
72695	95	130	86	35	110	3615	TY10021CG

1" STANDARD LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72719	11/16	30	54	17	58	904	TY10008CG
72720	3/4	35	54	17	58	904	TY10008CG
72721	13/16	37.5	54	17	58	1130	TY10008CG
72722	7/8	39	54	17	58	1243	TY10008CG
72723	15/16	40.5	54	17	58	1469	TY10008CG
72724	1	42.5	54	17	60	1582	TY10008CG
72725	1-1/16	44.5	54	17	60	1695	TY10008CG
72726	1-1/8	46	54	17	62	1924	TY10008CG
72727	1-3/16	49	54	17	62	2226	TY10008CG
72728	1-1/4	51.5	54	17	63	2486	TY10008CG
72729	1-5/16	54	54	19	66	2486	TY10008CG
72730	1-3/8	55	54	19	66	2486	TY10008CG
72731	1-7/16	56.5	54	19	66	2712	TY10008CG
72732	1-1/2	59	54	22	66	2712	TY10008CG
72733	1-9/16	61	54	22	66	2938	TY10008CG
72734	1-5/8	62.5	54	22	68	2938	TY10008CG
72735	1-11/16	65	54	25	70	3163	TY10008CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" STANDARD LENGTH IMPACT SOCKETS, CR-MO IMPERIAL CONTINUED



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72736	1-3/4	67.5	60.3	25	70	3163	TY10008CG
72737	1-13/16	69	60.3	27	72	3390	TY10008CG
72738	1-7/8	70	60.3	27	72	3390	TY10010CG
72739	1-15/16	72.5	60.3	27	76	3390	TY10010CG
72740	2	74	60.3	27	76	3616	TY10010CG
72741	2-1/16	76.5	60.3	31	80	3616	TY10010CG
72742	2-1/8	79	60.3	31	80	3616	TY10010CG
72743	2-3/16	80	60.3	31	84	3616	TY10010CG
72744	2-1/4	82.5	60.3	34	84	3616	TY10010CG
72745	2-5/16	84	60.3	34	84	3616	TY10010CG
72746	2-3/8	86.5	60.3	34	88	3616	TY10010CG
72747	2-7/16	89	60.3	36	88	3616	TY10010CG
72748	2-1/2	91.5	60.3	36	92	3616	TY10010CG
72749	2-9/16	92.5	60.3	38	92	3616	TY10010CG
72750	2-5/8	95	60.3	38	92	3616	TY10010CG
72751	2-11/16	96.5	60.3	38	96	3616	TY10010CG
72752	2-3/4	99	60.3	38	96	3616	TY10010CG
72753	2-13/16	101.5	60.3	41	96	3616	TY10010CG
72754	2-7/8	102.5	60.3	41	96	3616	TY10010CG
72755	2-15/16	104.5	60.3	41	100	3616	TY10010CG
72756	3	106.5	60.3	44	100	3616	TY10010CG
72757	3-1/16	109	60.3	44	100	3616	TY10010CG
72758	3-1/8	111	60.3	44	100	3616	TY10010CG
72759	3-1/4	115	86	44	102	3616	TY10021CG
72760	3-3/8	119	86	49	106	3616	TY10021CG
72761	3-1/2	124	86	49	108	3616	TY10021CG
72762	3-5/8	127	86	53	110	3616	TY10021CG
72763	3-3/4	130	86	53	110	3616	TY10021CG
72764	3-7/8	136	95	56	115	3616	
72765	4	140	95	56	115	3616	
72766	4-1/8	143	95	59	120	3616	
72767	4-1/4	146	95	59	120	3616	
72768	4-3/8	149	95	61	120	3616	
72769	4-1/2	152	95	61	120	3616	

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" DEEP LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72819	19	35	54	25	90	900	TY10008CG
72820	20	36	54	25	90	900	TY10008CG
72821	21	37.5	54	25	90	900	TY10008CG
72822	22	39	54	25	90	1240	TY10008CG
72823	23	40	54	25	90	1240	TY10008CG
72824	24	41.5	54	25	90	1470	TY10008CG
72825	25	42.5	54	25	90	1470	TY10008CG
72826	26	44	54	25	90	1470	TY10008CG
72827	27	45	54	25	90	1695	TY10008CG
72828	28	46.5	54	25	90	1955	TY10008CG
72829	29	47.5	54	25	90	1955	TY10008CG
72830	30	49	54	25	90	2225	TY10008CG
72831	31	50	54	25	90	2225	TY10008CG
72832	32	51.5	54	25	90	2490	TY10008CG
72833	33	52.5	54	25	90	2490	TY10008CG
72834	34	54	54	25	90	2490	TY10008CG
72835	35	55	54	25	90	2490	TY10008CG
72836	36	56.5	54	25	90	2712	TY10008CG
72837	37	58	54	25	90	2712	TY10008CG
72838	38	59	54	25	90	2712	TY10008CG
72839	39	60	54	25	90	2712	TY10008CG
72840	40	61	54	25	90	2712	TY10008CG
72841	41	62.5	54	25	90	2940	TY10008CG
72842	42	64	54	25	90	2940	TY10008CG
72843	43	65	54	25	90	2940	TY10008CG
72844	44	66	60.3	30	100	2940	TY10008CG
72845	45	67.5	60.3	30	100	2940	TY10008CG
72846	46	69	60.3	30	100	3390	TY10008CG
72847	47	70	60.3	30	100	3390	TY10008CG
72848	48	71.5	60.3	30	100	3390	TY10008CG
72849	49	73	60.3	30	100	3390	TY10008CG
72850	50	74	60.3	30	100	3615	TY10008CG
72851	51	75	60.3	30	100	3615	TY10010CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" DEEP LENGTH IMPACT SOCKETS, CR-MO METRIC CONTINUED



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72852	52	76.5	60.3	30	100	3615	TY10010CG
72853	53	78	60.3	35	100	3615	TY10010CG
72854	54	79	60.3	35	108	3615	TY10010CG
72855	55	80	60.3	35	108	3615	TY10010CG
72856	56	81.5	60.3	35	108	3615	TY10010CG
72857	57	82.5	60.3	35	108	3615	TY10010CG
72858	58	84	60.3	35	108	3615	TY10010CG
72859	59	85	60.3	35	108	3615	TY10010CG
72860	60	86.5	60.3	35	108	3615	TY10010CG
72862	62	88	60.3	35	120	3615	TY10010CG
72863	63	90	60.3	35	120	3615	TY10010CG
72865	65	92.5	60.3	35	120	3615	TY10010CG
72867	67	95	60.3	35	120	3615	TY10010CG
72868	68	96.5	60.3	35	120	3615	TY10010CG
72869	69	98	60.3	35	120	3615	TY10010CG
72870	70	99	60.3	35	125	3615	TY10010CG
72871	71	100	60.3	35	125	3615	TY10010CG
72875	75	105	60.3	35	125	3615	TY10010CG
72877	77	108	60.3	35	125	3615	TY10021CG
72880	80	111.5	60.3	35	125	3615	TY10021CG
72885	85	115	86	35	135	3615	TY10021CG
72890	90	124	86	35	135	3615	TY10021CG
72895	95	130	86	35	140	3615	TY10021CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" DEEP LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72919	1 1/16	30	54	25	90	904	TY10008CG
72920	3/4	35	54	25	90	904	TY10008CG
72921	13/16	37	54	25	90	1130	TY10008CG
72922	7/8	39	54	25	90	1243	TY10008CG
72923	15/16	40.5	54	25	90	1469	TY10008CG
72924	1	42.5	54	25	90	1582	TY10008CG
72925	1-1/16	44.5	54	25	90	1695	TY10008CG
72926	1-1/8	46	54	25	90	1924	TY10008CG
72927	1-3/16	49	54	25	90	2226	TY10008CG
72928	1-1/4	51.5	54	25	90	2486	TY10008CG
72929	1-5/16	54	54	25	90	2486	TY10008CG
72930	1-3/8	55	54	25	90	2486	TY10008CG
72931	1-7/16	56.5	54	25	90	2486	TY10008CG
72932	1-1/2	59	54	25	90	2486	TY10008CG
72933	1-9/16	61	54	25	90	2938	TY10008CG
72934	1-5/8	62.5	54	25	90	2938	TY10008CG
72935	1-11/16	65	54	25	90	3163	TY10008CG
72936	1-3/4	67.5	60.3	31	100	3163	TY10008CG
72937	1-13/16	69	60.3	31	100	3389	TY10008CG
72938	1-7/8	70	60.3	31	100	3389	TY10010CG
72939	1-15/16	72.5	60.3	31	100	3389	TY10010CG
72940	2	74	60.3	31	100	3616	TY10010CG
72941	2-1/16	76.5	60.3	31	100	3616	TY10010CG
72942	2-1/8	79	60.3	31	108	3616	TY10010CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" DEEP LENGTH IMPACT SOCKETS, CR-MO IMPERIAL CONTINUED



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72943	2-3/16	80	60.3	31	108	3616	TY10010CG
72944	2-1/4	82.5	60.3	36	108	3616	TY10010CG
72945	2-5/16	84	60.3	36	108	3616	TY10010CG
72946	2-3/8	86.5	60.3	36	108	3616	TY10010CG
72947	2-7/16	89	60.3	36	108	3616	TY10010CG
72948	2-1/2	91.5	60.3	36	120	3616	TY10010CG
72949	2-9/16	92.5	60.3	36	120	3616	TY10010CG
72950	2-5/8	95	60.3	44	120	3616	TY10010CG
72951	2-11/16	96.5	60.3	44	120	3616	TY10010CG
72952	2-3/4	99	60.3	44	125	3616	TY10010CG
72953	2-13/16	101.5	60.3	44	125	3616	TY10010CG
72954	2-7/8	102.5	60.3	44	125	3616	TY10010CG
72955	2-15/16	104.5	60.3	44	125	3616	TY10010CG
72956	3	106.5	60.3	44	125	3616	TY10010CG
72957	3-1/16	109	60.3	44	125	3616	TY10010CG
72958	3-1/8	111.5	60.3	44	125	3616	TY10010CG
72959	3-1/4	115	86	44	135	3616	TY10021CG
72960	3-3/8	119	86	56	135	3616	TY10021CG
72961	3-1/2	124	86	56	135	3616	TY10021CG
72962	3-5/8	127	86	56	140	3616	TY10021CG
72963	3-3/4	130	86	56	140	3616	TY10021CG
72964	3-7/8	136	95	56	140	3616	
72965	4	140	95	56	155	3616	
72966	4-1/8	143	95	61	155	3616	
72967	4-1/4	146	95	61	155	3616	
72968	4-3/8	149	95	61	155	3616	
72969	4-1/2	152	95	61	155	3616	

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1-1/2" STANDARD LENGTH IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72550	30	56	86	21	78	1706	TY10020CG
72551	32	58	86	22	78	1706	TY10020CG
72552	36	64	86	24	78	1706	TY10020CG
72549	38	66	86	21	78	1706	TY10020CG
72553	41	70	86	28	80	1706	TY10020CG
72554	46	76	86	30	84	1706	TY10020CG
72555	50	81	86	32	87	1706	TY10020CG
72556	55	87	86	37	90	1706	TY10020CG
72557	60	94	86	39	95	1706	TY10020CG
72558	65	100	86	42	100	1706	TY10020CG
72559	70	106	86	46	105	1706	TY10020CG
72560	75	112	86	49	108	5423	TY10020CG
72561	80	116	86	43	110	5423	TY10020CG
72562	85	125	86	56	118	5423	TY10020CG
72563	90	131	86	59	123	5423	TY10020CG
72564	95	137	95	61	123	5423	TY10025CG
72565	100	144	95	65	130	5423	TY10025CG
72566	105	154	95	68	130	5423	TY10025CG
72567	110	157	95	72	135	5423	TY10025CG
72568	115	164	95	77	140	5423	TY10025CG
72569	120	168	95	64	135	5423	TY10025CG
72571	130	184	127	80	145	5423	TY10025CG
72572	135	194	127	85	150		
72573	140	197	127	90	160		
72574	145	204	127	90	160		
72575	150	207	127	90	160		
72576	155	214	127	90	160		

1-1/2" STANDARD LENGTH IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72577	1-3/16	56	86	20	78		
72578	1-3/8	62	86	20	78		
72579	1-7/16	64	86	20	78		
72580	1 1/4	56	86	20	78		
72581	1-1/2	66	86	21	78	1706	TY10020CG
72582	1-3/4	75	86	24	84	1706	TY10020CG
72583	1-13/16	76	86	24	84	1706	TY10020CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1-1/2" STANDARD LENGTH IMPACT SOCKETS, CR-MO IMPERIAL CONTINUED



PART NO.	SIZE (inches)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72584	2	82	86	26	87	1706	TY10020CG
72585	2-1/16	83	86	27	87	5423	TY10020CG
72586	2-3/16	86	86	35	90	5423	TY10020CG
72587	2-5/16	92	86	36	92	5423	TY10020CG
72594	2-3/8	93	86	36	92	5423	TY10020CG
72588	2-7/16	96	86	38	95	5423	TY10020CG
72589	2-9/16	97	86	38	95	5423	TY10020CG
72595	2-5/8	103	86	41	100	5423	TY10020CG
72590	2-11/16	104	86	41	100	5423	TY10020CG
72596	2-15/16	110	86	41	103	5423	TY10020CG
72591	3	110	86	41	103	5423	TY10020CG
72597	3-1/8	116	86	43	110	5423	TY10025CG
72592	3-3/8	125	86	43	118	5423	TY10025CG
72593	3-1/2	130	86	47	118	5423	TY10025CG
72598	3-5/8	134	86	52	118		
72599	3-7/8	142	95	54	125		
72600	4	145	95	54	125		
72601	4-1/8	150	95	54	125		
72602	4-3/8	160	95	54	125		
72603	4-3/4	168	95	62	135		

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1/2" HEX DRIVERS IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D2 (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72475	5	25	78	30	
72476	6	25	78	52	
72477	7	25	78	78	
72478	8	25	78	120	
72479	10	25	78	220	
72480	11	25	78	295	
72481	12	25	78	370	
72482	14	25	78	590	
72483	17	25	78	1000	
72484	19	30	78	1400	

1/2" HEX DRIVERS IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D2 (mm)	L (mm)	TORQUE RATE N.M.	RET RING
72485	7/32	25	78	30	
72486	1/4	25	78	52	
72487	15/16	25	78	78	
72488	3/8	25	78	120	
72489	7/16	25	78	220	
72490	1/2	25	78	295	
72491	9/16	25	78	370	
72492	5/8	25	78	590	
72493	11/16	25	78	1000	
72494	3/4	30	78	1400	

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

3/4" HEX DRIVERS IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
72414	14	44	20	100	590	TY10032CG
72417	17	44	20	100	1000	TY10032CG
72419	19	44	20	100	1400	TY10032CG
72421	21	44	20	100	1867	TY10032CG
72422	22	44	20	100	2100	TY10032CG
72424	24	44	20	100	2700	TY10032CG
72427	27	44	20	100	2700	TY10032CG
72430	30	44	20	100	2700	TY10032CG
72432	32	44	20	100	2700	TY10032CG

3/4" HEX DRIVERS IMPACT SOCKETS, CR-MO IMPERIAL



PART NO.	SIZE (inches)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
72439	9/16	44	20	100	590	TY10032CG
72440	5/8	44	20	100	865	TY10032CG
72442	3/4	44	20	100	1400	TY10032CG
72443	13/16	44	20	100	1867	TY10032CG
72444	7/8	44	20	100	2100	TY10032CG
72445	15/16	44	20	100	2700	TY10032CG
72446	1	44	20	100	2700	TY10032CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" HEX DRIVERS IMPACT SOCKETS, CR-MO METRIC



PART NO.	SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
72514	14	54	20	100	590	
72517	17	54	20	100	1000	
72519	19	54	20	100	1400	
72522	22	54	20	100	2100	
72524	24	54	20	100	2700	
72527	27	54	20	100	2700	
72530	30	54	20	100	2700	
72532	32	54	20	100	2700	

IMPACT UNIVERSAL JOINT, CR-MO



PART NO.	(FULL SQ) SIZE (inch)	(EMPTY SQ) SIZE (inch)	D2 (mm)	L (mm)	TORQUE RATE N.M.
72450	1/2	1/2	27.6	65.6	316
72451	3/4	3/4	44	111.5	791
72470	1	1	54	133	1130

IMPACT ADAPTOR, CR-MO



PART NO.	(FULL SQ) SIZE (inch)	(EMPTY SQ) SIZE (inch)	D2 (mm)	L (mm)	TORQUE RATE N.M.
72452	3/8	1/2	22.5	37	226
72453	1/2	3/8	25	38	226
72454	1/2	3/4	29.8	47	508
72455	3/4	1/2	44	56	508
72456	3/4	1"	44	63	1582
72457	1	3/4	54	73	1582
72471	1	1-1/2	51	86.5	1910
72472	1-1/2	1	86	100	1910

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

IMPACT EXTENSION BAR, CR-MO



PART NO.	(FULL SQ) SIZE (inch)	(EMPTY SQ) SIZE (inch)	L (inches)	D2 (mm)	L (mm)	TORQUE RATE N.M.
72458	1/2	1/2	3	24	76	395
72459	1/2	1/2	5	24	127	395
72460	1/2	1/2	10	24	252	395
72461	3/4	3/4	7	44	175	1017
72462	3/4	3/4	10	44	252	1017
72466	1	1	3	54	76	1695
72467	1	1	7	54	175	1695
72468	1	1	10	54	252	1695
72469	1	1	13	54	328	1695

3/4" DR RECTANGLE IMPACT SOCKETS



PART NO.	STD/DEEP	SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
72200	STD	19 X 21	44	45	27		TY10032CG
72201	DEEP	19 X 21	44	45	34		TY10032CG
72202	STD	21 X 28	44	50	27		TY10034CG
72203	DEEP	21 X 28	44	50	34		TY10034CG

1" DR RECTANGLE IMPACT SOCKETS



PART NO.	STD/DEEP	SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
72615	STD	19 X 21	47	54	29		TY10008CG
72616	DEEP	19 X 21	47	54	35		TY10008CG
72617	STD	21 X 28	62	62	29		TY10010CG
72618	DEEP	21 X 28	62	62	35		TY10010CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

1" DR TORX IMPACT SOCKETS



PART NO.	SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
72980	E20	33.5	54	16		TY10008CG
72984	E24	33.5	54	16		TY10008CG

1/2" WHEEL NUT IMPACT SOCKET WITH PLASTIC SLEEVE & STOP, CR-MO METRIC



PART NO.	SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.
72001	17 BLUE	27	30	14	85	475
72002	19 YELLOW	29	30	15	85	565
72003	21 RED	31	30	17	85	570
72004	22 PURPLE	32.5	32	18	85	570
72005	24 GREEN	35	34	18	85	570

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

14 PC 1/2" DR. STANDARD IMPACT SOCKET SET METRIC PART NO. 72500



SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
10	17	25	6	38	153	
11	18	25	8	38	170	
12	19	25	8	38	203	
13	21	25	8	38	249	
14	22	25	8	38	282	
15	23	30	9	38	339	TYRR50095
16	24	30	9	38	407	TYRR50095
17	26	30	9	38	475	TYRR50095
18	27	30	9	38	542	TYRR50095
19	28	30	10	38	565	TYRR50095
21	30	30	12	38	570	TYRR50095
22	32	30	12	38	570	TYRR50095
24	36	30	14	43	570	TYRR50095
27	38	30	14	43	570	TYRR50095

13 PC 1/2" DR. STANDARD IMPACT SOCKET SET IMPERIAL PART NO. 72502



SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
7/16	18.5	25	9	38	226	
1/2	20.5	25	9	38	294	
9/16	23	25	11	38	373	
5/8	24.5	30	11	38	463	TYRR50095
11/16	27	30	11	38	565	TYRR50095
3/4	28	30	11	38	565	TYRR50095
13/16	30	30	11	38	565	TYRR50095
7/8	31.8	30	13	38	565	TYRR50095
15/16	33.8	30	13	38	565	TYRR50095
1	35.8	30	13	40	565	TYRR50095
1-1/16	37.8	30	13	43	565	TYRR50095
1-1/8	39.8	30	16.5	43	565	TYRR50095
1-1/4	43.8	30	16.5	43	565	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

14 PC 1/2" DR. DEEP IMPACT SOCKET SET METRIC PART NO.72501



SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
10	17	25	11	80	153	
11	18.5	25	11	80	170	
12	20	25	11	80	203	
13	21	25	11	80	249	
14	22.4	25	11	80	282	
15	23	30	11	80	339	TYRR50095
16	25	30	11	80	407	TYRR50095
17	26	30	11	80	475	TYRR50095
18	27.5	30	11	80	542	TYRR50095
19	28.5	30	13	80	565	TYRR50095
21	31.9	30	13	80	570	TYRR50095
22	31.8	30	13	80	570	TYRR50095
24	35.8	30	15	80	570	TYRR50095
27	37.8	30	18.3	80	570	TYRR50095

13 PC 1/2" DR. DEEP IMPACT SOCKET SET IMPERIAL PART NO. 72503



SIZE (mm)	D1 (mm)	D2 (mm)	T (mm)	L (mm)	TORQUE RATE N.M.	RET RING
7/16	18.5	25	14	78	226	
1/2	20.5	25	14	78	294	
9/16	23	25	14	78	373	
5/8	24.5	30	14	78	463	TYRR50095
11/16	27	30	17	78	565	TYRR50095
3/4	28	30	17	78	565	TYRR50095
13/16	29.8	30	17	78	565	TYRR50095
7/8	31.8	30	19	78	565	TYRR50095
15/16	33.8	30	19	78	565	TYRR50095
1	35.8	30	19	78	565	TYRR50095
1-1/16	37.8	30	19	78	565	TYRR50095
1-1/8	39.8	30	19	78	565	TYRR50095
1-1/4	43.8	30	30	78	565	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

28 PC 1/2" DRIVE STANDARD & DEEP IMPACT SOCKET SET METRIC PART NO. 72506



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
STD 10	17	25	6	38	153	
STD 11	18	25	8	38	170	
STD 12	19	25	8	38	203	
STD 13	21	25	8	38	249	
STD 14	22	25	8	38	282	
STD 15	23	30	9	38	339	TYRR50095
STD 16	24	30	9	38	407	TYRR50095
STD 17	26	30	9	38	475	TYRR50095
STD 18	27	30	9	38	542	TYRR50095
STD 19	28	30	10	38	565	TYRR50095
STD 21	30	30	12	38	570	TYRR50095
STD 22	32	30	12	38	570	TYRR50095
STD 24	34	30	14	40	570	TYRR50096
STD 27	38	30	14	43	570	TYRR50095
DEEP 10	17	25	11	80	153	
DEEP 11	18.5	25	11	80	170	
DEEP 12	20	25	11	80	203	
DEEP 13	21	25	11	80	249	
DEEP 14	22.4	25	11	80	282	
DEEP 15	23	30	11	80	339	TYRR50095
DEEP 16	25	30	11	80	407	TYRR50095
DEEP 17	26	30	11	80	475	TYRR50095
DEEP 18	27.5	30	11	80	542	TYRR50095
DEEP 19	28.5	30	13	80	565	TYRR50095
DEEP 21	31.9	30	13	80	570	TYRR50095
DEEP 22	31.8	30	13	80	570	TYRR50095
DEEP 24	34.8	30	15	80	570	TYRR50095
DEEP 27	37.8	30	18.3	80	570	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

26 PC 1/2" DRIVE STANDARD & DEEP IMPACT SOCKET SET IMPERIAL PART NO.72507



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
STD 7/16	18.5	25	9	38	226	
STD 1/2	20.5	25	9	38	294	
STD 9/16	23	25	11	38	373	
STD 5/8	24.5	30	11	38	463	TYRR50095
STD 11/16	27	30	11	38	565	TYRR50095
STD 3/4	28	30	11	38	565	TYRR50095
STD 13/16	30	30	11	38	565	TYRR50095
STD 7/8	31.8	30	13	38	565	TYRR50095
STD 15/16	33.8	30	13	38	565	TYRR50095
STD 1	35.8	30	13	40	565	TYRR50095
STD 1-1/16	37.8	30	13	43	565	TYRR50095
STD 1-1/8	39.8	30	16.5	43	565	TYRR50095
STD 1-1/4	43.8	30	16.5	43	565	TYRR50095
DEEP 7/16	18.5	25	14	78	226	
DEEP 1/2	20.5	25	14	78	294	
DEEP 9/16	23	25	14	78	373	
DEEP 5/8	24.5	30	14	78	463	TYRR50095
DEEP 11/16	27	30	17	78	565	TYRR50095
DEEP 3/4	28	30	17	78	565	TYRR50095
DEEP 13/16	29.8	30	17	78	565	TYRR50095
DEEP 7/8	31.8	30	19	78	565	TYRR50095
DEEP 15/16	33.8	30	19	78	565	TYRR50095
DEEP 1	35.8	30	19	78	565	TYRR50095
DEEP 1-1/16	37.8	30	19	78	565	TYRR50095
DEEP 1-1/8	39.8	30	19	78	565	TYRR50095
DEEP 1-1/4	43.8	30	30	78	565	TYRR50095

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

8 PC 3/4" STANDARD LENGTH IMPACT SOCKET SET METRIC PART NO. 72510



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
24	38.5	44	16	51	1085	TY10032CG
27	42.5	44	16	53	1580	TY10032CG
30	46	44	19	53	1885	TY10032CG
32	48.5	44	19	57	2030	TY10032CG
34	51	44	22	57	2030	TY10032CG
36	53.5	44	22	57	2030	TY10032CG
41	60	44	22	58	2030	TY10032CG
46	66	44	25	62	2030	TY10032CG

8 PC 3/4" STANDARD LENGTH IMPACT SOCKET SET IMPERIAL PART NO. 72512



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
1	40	41.4	13	53	1243	TY10032CG
1-1/16	42.5	44	13	53	1582	TY10032CG
1-1/8	44	44	16	53	1808	TY10032CG
1-1/4	48	44	16	57	2034	TY10032CG
1-5/16	50	44	19	57	2034	TY10032CG
1-3/8	52.5	44	19	57	2034	TY10032CG
1-7/16	53.5	44	19	57	2034	TY10032CG
1-1/2	56	44	22	57	2034	TY10032CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

8 PC 3/4" DEEP LENGTH IMPACT SOCKET SET METRIC PART NO. 72511



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
24	38.5	44	19	90	1085	TY10032CG
27	42.5	44	22	90	1580	TY10032CG
30	46	44	22	90	1885	TY10032CG
32	48.5	44	22	90	2030	TY10032CG
34	51	44	25	90	2030	TY10032CG
36	53.5	44	25	90	2030	TY10032CG
41	60	44	30	90	2030	TY10032CG
46	66	44	30	90	2030	TY10032CG

8 PC 3/4" DEEP LENGTH IMPACT SOCKET SET IMPERIAL PART NO. 72513



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
1	40	41.4	16	90	1243	TY10032CG
1-1/16	42.5	44	16	90	1582	TY10032CG
1-1/8	44	44	16	90	1808	TY10032CG
1-1/4	48.5	44	16	90	2034	TY10032CG
1-5/16	50	44	22	90	2034	TY10032CG
1-3/8	52.5	44	22	90	2034	TY10032CG
1-7/16	53.5	44	22	90	2034	TY10032CG
1-1/2	56	44	22	90	2034	TY10032CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

9 PC 1" STANDARD LENGTH IMPACT SOCKET SET METRIC PART NO. 72612



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
24	41.5	54	17	58	1470	TY10008CG
27	45	54	17	60	1695	TY10008CG
30	49	54	19	62	2225	TY10008CG
32	51.5	54	19	63	2490	TY10008CG
36	56.5	54	23	66	2712	TY10008CG
38	59	54	23	66	2712	TY10008CG
41	62.5	54	25	68	2940	TY10008CG
46	69	60.3	29	72	3390	TY10008CG
50	74	60.3	31	76	3615	TY10008CG

9 PC 1" STANDARD LENGTH IMPACT SOCKET SET IMPERIAL PART NO. 72610



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
1	42.5	54	17	60	1582	TY10008CG
1-1/8	46	54	17	62	1924	TY10008CG
1-1/4	51.5	54	17	63	2486	TY10008CG
1-5/16	54	54	19	66	2486	TY10008CG
1-1/2	59	54	22	66	2712	TY10008CG
1-5/8	62.5	54	22	68	2938	TY10008CG
1-3/4	67.5	60.3	25	70	3163	TY10008CG
1-7/8	70	60.3	27	72	3390	TY10010CG
2	74	60.3	27	76	3616	TY10010CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

9 PC 1" DEEP LENGTH IMPACT SOCKET SET METRIC PART NO. 72613



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
24	41.5	54	25	90	1470	TY10008CG
27	45	54	25	90	1695	TY10008CG
30	49	54	25	90	2225	TY10008CG
32	51.5	54	25	90	2490	TY10008CG
36	56.5	54	25	90	2712	TY10008CG
38	59	54	25	90	2712	TY10008CG
41	62.5	54	25	90	2940	TY10008CG
46	69	60.3	30	100	3390	TY10008CG
50	74	60.3	30	100	3615	TY10008CG

9 PC 1" STANDARD LENGTH IMPACT SOCKET SET IMPERIAL PART NO. 72611



SIZE (mm)	D1 (mm)	D2 (mm)	T (MM)	L (mm)	TORQUE RATE N.M.	RET RING
1	42.5	54	25	90	1582	TY10008CG
1-1/8	46	54	25	90	1924	TY10008CG
1-1/4	51.5	54	25	90	2486	TY10008CG
1-5/16	54	54	25	90	2486	TY10008CG
1-1/2	59	54	25	90	2486	TY10008CG
1-5/8	62.5	54	25	90	2938	TY10008CG
1-3/4	67.5	60.3	31	100	3163	TY10008CG
1-7/8	70	60.3	31	100	3389	TY10010CG
2	74	60.3	31	100	3616	TY10010CG

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

8 PC 1/2" HEX DRIVERS IMPACT SOCKET SET METRIC PART NO. 72504



SIZE (mm)	D2 (mm)	L (mm)	TORQUE RATE N.M.	RET RING
10	25	78	220	
11	25	78	295	
12	25	78	370	
14	25	78	590	
15				
17	25	78	1000	
19	30	78	1400	

8 PC 1/2" HEX DRIVERS IMPACT SOCKET SET IMPERIAL PART NO. 72505



SIZE (mm)	D2 (mm)	L (mm)	TORQUE RATE N.M.	RET RING
1/4	25	78	52	
15/16	25	78	78	
3/8	25	78	120	
7/16	25	78	220	
1/2	25	78	295	
9/16	25	78	370	
5/8	25	78	590	
3/4	30	78	1400	

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

7 PC 3/4" DRIVE INHEX IMPACT SOCKET SET METRIC PART NO. 72410



SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
19	44	20	100	1400	
21	44	20	100	1867	
22	44	20	100	2100	
24	44	20	100	2700	
27	44	20	100	2700	
30	44	20	100	2700	
32	44	20	100	2700	

8 PC 3/4" DRIVE INHEX IMPACT SOCKET SET IMPERIAL PART NO. 72412



SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
9/16	44	20	100	590	TY10032CG
5/8	44	20	100	865	TY10032CG
11/16	44	20	100		TY10032CG
3/4	44	20	100	1400	TY10032CG
13/16	44	20	100	1867	TY10032CG
7/8	44	20	100	2100	TY10032CG
15/16	44	20	100	2700	TY10032CG
1	44	20	100	2700	TY10032CG

7 PC 3/4" DRIVE INHEX IMPACT SOCKET SET METRIC PART NO. 72509



SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
14	44	20	100	590	
17	44	20	100	1000	
19	44	20	100	1400	
21	44	20	100	1867	
22	44	20	100	2100	
24	44	20	100	2700	
27	44	20	100	2700	

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

7 PC 1" INHEX IMPACT SOCKET SET METRIC PART NO. 72614



SIZE (mm)	D2 (mm)	L (mm)	L2 (mm)	TORQUE RATE N.M.	RET RING
14	54	20	100	590	
17	54	20	100	1000	
19	54	20	100	1400	
21	54	20	100		
22	54	20	100	2100	
24	54	20	100	2700	
27	54	20	100	2700	

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.

RETAINING RINGS



PART NO.	SIZE (mm)
TY10005CG	RR 3/4" DR - 1-1/4"
TY10008CG	RR 1" DR 19-50MM / 11/16" - 1-13/16"
TY10010CG	RR 1" DR 51-75MM / 1-7/8" - 3-1/8"
TY10015CG	RR 1" DR 2-1/8"
TY10016CG	RR 1" DR 2-1/4"
TY10017CG	RR 1" DR 2-1/2"
TY10019CG	RR 1" DR 2-5/8"
TY10020CG	RR 1-1/2" DR 30-90MM / 1-1/4" - 3"
TY10021CG	RR 1-1/2" DR 77-95MM / 3-1/4" - 3-5/8"
TY10025CG	RR 1-1/2" DR 95-115MM / 3-3/8" - 3-1/2"
TY10030CG	RR 1-1/2" DR 3-7/8"
TY10032CG	RR 3/4" DR 17-50MM / 1/2" - 2"
TY10034CG	RR 3/4" DR 1-5/8"
TY10035CG	RR 1-1/2" DR 130-130MM
TY18708CG	RR 3/4" DR 54-65MM / 2-1/16" - 2-1/2"
TY18710CG	RR 3/4" DR 2"
TY18715CG	RR 3/4" DR 2-1/8"
TY18716CG	RR 3/4" DR 2-1/4"
TYRR50095	RR 1/2" DR 15-38MM / 5/8" - 1-1/4"

CAUTION Always wear safety goggles when using impact equipment. Do not hold socket while in use.



OUR GUARANTEE OF STRENGTH

Typhoon Tools have a lifetime warranty against faulty workmanship and materials.

 typhoontoolsaustralia
www.typhoon-tools.com.au

HEAD OFFICE

Phone 03 8353 2402 Fax 03 8353 2403
39 Sunline Drive, Truganina, Victoria 3029
salesvic@typhoon-tools.com.au

WESTERN AUSTRALIA

Phone 08 9258 8999 Fax 08 9358 0555
1/14 Fargo Way, Welshpool WA 6106
sales@typhoon-tools.com.au