



Representative Photo Only  
(actual product may vary based on configuration selections)

### 3 Way Jumper For Series 2002

Stripped solid conductors, stranded conductors with ferruls or ultrasonically "bonded" conductors are easily connected by simply pushing the wire into the wire entry. Utilising only a screwdriver to open the clamp, this represents a significant time and cost saving. For conductors between 0.5mm<sup>2</sup> and 16mm<sup>2</sup>, 2, 3, 4 conductor terminal blocks, Double deck and triple terminal blocks plus fuse and disconnect terminals.

#### SPECIFICATIONS

Component Type Termination Wiring	Jumper
Compatible Product Series'	2002
In, Rated Current	25 A
Colour	Light Grey
Fire Load	0.01 MJ
Height	4.1 mm
Width	13.8 mm
Depth	19 mm
Weight	0.001395 kg
Certifications	RoHS

#### REFERENCES

IECEx Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	<a href="#">2002403_Manufacturer Catalogue</a>

Catalogue No: **2002-403**

## PUSH-IN JUMPER 2002 SERIES 3 WAY LIGHT GREY

Termination and Wiring Systems > Terminals and Pre-Wired Cables > Terminals - Screwless > WAGO Screwless Terminals > Series 2002 - 2.5mm<sup>2</sup> TOPJOB S Terminals > Series 2002 - Accessories

