




Item no.	285-407 	GTIN / EAN	4045454326241
Content	1 piece	Order unit	piece
Order quantity	<input type="text" value="5"/> piece	Increase in order quantity	(5, 10, 15, 20, ...)
Customer item no.		Customs Tariff no.	85366990990
Customs duty for the country of origin	PL	Available	-
List price	On request	Net price	On request
Availability	On request		

**Note: Some items may not be available from your local WAGO company.**

**Please note that the quantities ordered in the shopping cart are rounded up to the PU (SPU).**

**Power tap; for 95 mm<sup>2</sup> high-current terminal blocks**

RoHS ✓  
Compliant

Article details

Approbations

Downloads

**Description  
Remarks**

Power tap; for 95 mm<sup>2</sup> high-current terminal blocks

**Item  
properties**

**Miscellaneous**

<b>Name</b>	<b>Value</b>	<b>Unit</b>
Total number of connection points	2	
Total number of potentials	2	
Color	gray	
Ratings according to 1	IEC/EN 60947-7-1	
Pollution degree (1)	3	
Rated voltage EN (1) [V]	1000	V
Rated surge voltage (1) [kV]	8	kV
Nominal current [A]	57	A
Connection technology (1)	CAGE CLAMP®	
Solid sizes 1	0.2 ... 10 mm <sup>2</sup> / 24 ... 8 AWG	
Fine-stranded wires 1	0.2 ... 10 mm <sup>2</sup> / 24 ... 8 AWG	
Strip length 1	12 ... 13 mm / 0.47 ... 0.51 in	

**Power tap; for 95 mm<sup>2</sup> high-current terminal blocks**

Type of wiring	Front-entry wiring	
Design	angled	
Marking level	Center marking	
Fire load [MJ]	0.249	MJ
Weight [g]	22.81	g
Width	20 mm / 0.787 in	
Height	20 mm / 0.787 in	
Module width [mm]	20	mm
Module width [inch] [inch]	0.787	inch

[Upwards](#)