

Filter Performance Data - 0.2 Micron

HEALTH CLAIM PERFORMANCE CERTIFIED BY NSF/ANSI

This system has been tested according to AS3497, NSF/ANSI Standards 42, 53 and 401 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42, 53 and 401.

93701, 93702, 93704	NHMRC ADWG or USEPA SDWA MCL	Average Influent concentration	NSF/ANSI influent challenge concentration	% reduction reqt / Max. permissible product water concentration	Max effluent concentration	Minimum % reduction	Average % removal	Average effluent concentration
NSF/ANSI 42 - Aesthetic Effects								
Chlorine, Taste and Odor	0.6 mg/L	1.92 mg/L	2.0 mg/L ± 10%	≥ 50%	0.06 mg/L	96.8%	97.4%	0.05 mg/L
Nominal Particulate Reduction, Class I (≥ 0.5 µm to < 1 µm)	-	9,200,000 particles/mL	at least 10,000 particles/mL	≥ 85%	190,000 particles/mL	98.2%	99.0%	96,167 particles/mL
NSF/ANSI 53 - Health Effects								
Cysts (3.00 ± 0.15 µm particles)	99.5% reduction	125,000 microspheres/L	minimum 50,000 microspheres/L	≥ 99.95%	8 microspheres/L	99.99%	99.99%	8 microspheres/L
Lead (at 6.5 pH)	-	0.155 mg/L	0.15 mg/L ± 10%	0.005 mg/L	0.0015 mg/L	99.0%	99.8%	0.0003 mg/L
Lead (at 8.5 pH)	-	0.162 mg/L	0.15 mg/L ± 10%	0.005 mg/L	0.0019 mg/L	98.7%	99.6%	0.0006 mg/L
Asbestos	7 MFL	20,144,750 fibers/L	10 ⁷ to 10 ⁸ fibers/L (10 - 100 MFL)	≥ 99%	650 fibers/L	99.99%	99.99%	157 fibers/L
Total PFAS (Only applied to 93701 and 93702 cartridges)	0.02 ug/L	2.190 µg/L	2.16 ± 20% µg/L	0.02 µg/L	0.019 µg/L	99.12%	99.43%	0.012 µg/L
NSF/ANSI 401 -Emerging Compounds/Incidental Contaminants								
Microplastics, particles 0.5 to < 1 µm	-	9,200,000 particles/mL	at least 10,000 particles/mL	≥ 85%	190,000 particles/mL	98.2%	99.0%	96,167 particles/mL

*Pressure = 60 psig ± 3; pH = 7.5 ± 0.5; temp. = 20° ± 3°C *United States Environmental Protection Agency (USEPA) Safe Drinking Water Act / New Zealand Ministry of Health Drinking-water Standards for New Zealand

Category	Treatment Type	Function	Pass
I	Microbiological Status	Will stop bacteria increasing, but will not remove unless II (a) is passed.	✓
II	Microbiological Treatment		
II (a)	Bacteria Removal	Will remove or inactivate bacteria.	N/A
II (b)	Virus Removal	Will remove or inactivate virus.	N/A
II (c)	Protozoa Removal	Cyptosporidium and Giardia. Will not remove or inactivate bacteria unless II (a) and II (b) are passed.	✓
III	Particulate Reduction	Reduces cloudiness.	✓
IV	Taste and Odour Reduction	Reduces tastes and odours.	✓
V	Chemical Treatment	Decreases certain chemicals: - Chlorine - Lead - Total PFAS (Only applied to 93701 and 93702 cartridges)	✓

Legend: = ✓ Pass N/A = Not Applicable

OPERATING SPECIFICATIONS

- Pressure requirement: 10 -125 psi (0.7 - 8.62 bar), non-shock
- Temperature: 35 -100°F (2-38°C)

Model	Flow Rate	Capacity	Kit #
0.2mic MicroPurity Filter 1S	3.75 Lpm	4,100 L	93701
0.2mic MicroPurity filter 1.5S	3.75 Lpm	5,500 L	93702
0.2mic MicroPurity Filter 2S	5.678 Lpm	9,463 L	93704

Zip filter systems are designed for ease of installation. However, post-installation inspections are highly recommended. Check for leaks immediately after installation and once again after 24 hours. If leaks are detected, turn off water supply, drain water and inspect the leaks. If problem persists, contact the installer / plumber for rectification.

It is essential that operational, maintenance and filter replacement requirements be carried out for this product to perform as advertised. Flush new cartridge for 10L or at least 2 min 40 seconds to remove trapped air bubbles.

If left unused for more than 48 hours, flush cartridge for 10L or at least 2 min 40 seconds before use.

The compounds certified under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'. Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

Note: While the testing was performed under standard laboratory conditions, actual performance may vary.

This 93701, 93702 and 93704 cartridge is certified by IAPMO R&T in PS-ZIP 0.2 micron system against NSF/ANSI Standard 42, 53 and 401 for the reduction of:

STANDARD NO. 42 – AESTHETIC EFFECTS

Bacteriostatic Effects
Chemical Reduction Unit
Taste and Odour Reduction
Chlorine Reduction
Mechanical Filtration Unit
Nominal Particulate Reduction, Class I

STANDARD NO. 53 – HEALTH EFFECTS

Chemical Reduction Unit
Lead Reduction
Total PFAS (Only applied to 93701 and 93702 cartridges)

Mechanical Filtration Unit
Cyst Reduction
Asbestos

STANDARD NO. 401 – Emerging Compounds/Incidental Contaminants

Microplastics

* The term "bacteriostatic" indicates that the system limits the passage or growth of bacteria that may already exist in the incoming water. It does not mean that water leaving the system is safer to drink than water entering the system.



*Filter system certified by IAPMO R&T against NSF 42, 53 and 401; against NSF 372 for lead free product. Models 93701 and 93702 are certified against CSA B483.1

Filter Performance Data - 3 Micron

HEALTH CLAIM PERFORMANCE CERTIFIED BY NSF/ANSI

This system has been tested according to AS3497, NSF/ANSI 42 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standard 42.

93703, 93705	NHMRC ADWG or USEPA SDWA MCL	Average Influent concentration	NSF/ANSI influent challenge concentration	% reduction reqt / Max. permissible product water concentration	Max effluent concentration	Minimum % reduction	Average % removal	Average effluent concentration
NSF/ANSI 42 - Aesthetic Effects								
Chlorine, Taste and Odor	0.6 mg/L	2.16 mg/L	2.0 mg/L ± 10%	≥ 50%	0.05 mg/L	97.7%	99.2%	0.02 mg/L
Nominal Particulate Reduction, Class II (1 µm to < 5 µm)	-	4,200,000 particles/mL	at least 10,000 particles/mL	≥ 85%	270,000 particles/mL	93.7%	97.7%	95,167 particles/mL

*Pressure = 60 psig ± 3; pH = 7.5 ± 0.5; temp. = 20° ± 3°C *United States Environmental Protection Agency (USEPA) Safe Drinking Water Act / New Zealand Ministry of Health Drinking-water Standards for New Zealand

Category	Treatment Type	Function	Pass
I	Microbiological Status	Will stop bacteria increasing, but will not remove unless II (a) is passed.	✓
II	Microbiological Treatment	Will remove or inactivate bacteria.	N/A
II (a)	Bacteria Removal		
II (b)	Virus Removal	Will remove or inactivate virus.	N/A
II (c)	Protozoa Removal	Cyptosporidium and Giardia. Will not remove or inactivate bacteria unless II (a) and II (b) are passed.	N/A
III	Particulate Reduction	Reduces cloudiness.	✓
IV	Taste and Odour Reduction	Reduces tastes and odours.	✓
V	Chemical Treatment	Decreases certain chemicals: - Chlorine	✓

Legend: = ✓ Pass N/A = Not Applicable

OPERATING SPECIFICATIONS

- Pressure requirement: 10 -125 psi (0.7 - 8.62 bar), non-shock
- Temperature: 35 -100°F (2-38°C)

Model	Flow Rate	Capacity	Kit #
3mic MicroPurity filter 1.5S	3.75 Lpm	13,248 L	93703
3mic MicroPurity Filter 2S	5.678 Lpm	17,034 L	93705

Zip filter systems are designed for ease of installation. However, post-installation inspections are highly recommended. Check for leaks immediately after installation and once again after 24 hours. If leaks are detected, turn off water supply, drain water and inspect the leaks. If problem persists, contact the installer / plumber for rectification.

It is essential that operational, maintenance and filter replacement requirements be carried out for this product to perform as advertised.

Flush new cartridge for 10L or at least 2 min 40 seconds to remove trapped air bubbles.

If left unused for more than 48 hours, flush cartridge for 10L or at least 2 min 40 seconds before use.

The compounds certified under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'. Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

Note: While the testing was performed under standard laboratory conditions, actual performance may vary.

This 93703 and 93705 cartridge is certified by IAPMO R&T in PS-ZIP 3 micron system against NSF/ANSI Standard 42 for the reduction of:

STANDARD NO. 42 – AESTHETIC EFFECTS

- Bacteriostatic Effects
- Chemical Reduction Unit
- Taste and Odour Reduction
- Chlorine Reduction
- Mechanical Filtration Unit
- Nominal Particulate Reduction, Class II

* The term "bacteriostatic" indicates that the system limits the passage or growth of bacteria that may already exist in the incoming water. It does not mean that water leaving the system is safer to drink than water entering the system.



*Filter system certified by IAPMO R&T against NSF 42; against NSF 372 for lead free product.

Filter Performance Data - Carbon Free

HEALTH CLAIM PERFORMANCE CERTIFIED BY NSF/ANSI

This system has been tested according to AS3497, NSF/ANSI Standards 42, 53 and 401 for the reduction of the substances listed below. The concentration of the indicated substances in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI Standards 42, 53 and 401.

93706	NHMRC ADWG or USEPA SDWA MCL	Average Influent concentration	NSF/ANSI influent challenge concentration	% reduction reqt / Max. permissible product water concentration	Max effluent concentration	Minimum % reduction	Average % removal	Average effluent concentration
NSF/ANSI 42 - Aesthetic Effects								
Nominal Particulate Reduction, Class I ($\geq 0.5 \mu\text{m}$ to $< 1 \mu\text{m}$)	-	17,033,333 particles/mL	at least 10,000 particles/mL	$\geq 85\%$	96,000 particles/mL	99.35%	99.66%	58,333 particles/mL
NSF/ANSI 53 - Health Effects								
Cysts ($3.00 \pm 0.15 \mu\text{m}$ particles)	99.5% reduction	90000 microspheres/L	minimum 50,000 microspheres/L	$\geq 99.95\%$	1.0 microspheres/L	99.99%	99.99%	1.0 microspheres/L
Asbestos	7 MFL	20,000,000 fibers/L	10^7 to 10^8 fibers/L (10 - 100 MFL)	$\geq 99\%$	< 1.0 fibers/L	$> 99.99\%$	$> 99.99\%$	< 1.0 fibers/L
NSF/ANSI 401 -Emerging Compounds/Incidental Contaminants								
Microplastics, particles 0.5 to $< 1 \mu\text{m}$	-	17,033,333 particles/mL	at least 10,000 particles/mL	$\geq 85\%$	96,000 particles/mL	99.30%	99.66%	58,333 particles/mL

*Pressure = 60 psig \pm 3; pH = 7.5 \pm 0.5; temp. = 20° \pm 3°C *United States Environmental Protection Agency (USEPA) Safe Drinking Water Act / New Zealand Ministry of Health Drinking-water Standards for New Zealand

Category	Treatment Type	Function	Pass
I	Microbiological Status	Will stop bacteria increasing, but will not remove unless II (a) is passed.	✓
II	Microbiological Treatment	Will remove or inactivate bacteria.	N/A
II (a)	Bacteria Removal		
II (b)	Virus Removal	Will remove or inactivate virus.	N/A
II (c)	Protozoa Removal	Cyptosporidium and Giardia. Will not remove or inactivate bacteria unless II (a) and II (b) are passed.	✓
III	Particulate Reduction	Reduces cloudiness.	✓
IV	Taste and Odour Reduction	Reduces tastes and odours.	N/A
V	Chemical Treatment	Decreases certain chemicals: - Lead	N/A

Legend: = ✓ Pass N/A = Not Applicable

OPERATING SPECIFICATIONS

- Pressure requirement: 10 -125 psi (0.7 - 8.62 bar), non-shock
- Temperature: 35 -100°F (2-38°C)

Model	Flow Rate	Kit #
0.2mic MicroPurity Filter 1.5S	5.678 Lpm	93706

Zip filter systems are designed for ease of installation. However, post-installation inspections are highly recommended. Check for leaks immediately after installation and once again after 24 hours. If leaks are detected, turn off water supply, drain water and inspect the leaks. If problem persists, contact the installer / plumber for rectification.

It is essential that operational, maintenance and filter replacement requirements be carried out for this product to perform as advertised.

Flush new cartridge for at least 6 minutes to remove trapped air bubbles.

If left unused for more than 48 hours, flush cartridge for 2 minutes before use.

The compounds certified under NSF/ANSI 401 have been deemed as 'incidental contaminants / emerging compounds'. Incidental contaminants are those compounds that have been detected in drinking water supplies at trace levels. While occurring at only trace levels, these compounds can affect the public acceptance/perception of drinking water quality.

Note: While the testing was performed under standard laboratory conditions, actual performance may vary.

This 93706 cartridge is certified by IAPMO R&T in PS-ZIP 0.2 micron system against NSF/ANSI Standard 42, 53 and 401 for the reduction of:

STANDARD NO. 42 – AESTHETIC EFFECTS

- Bacteriostatic Effects
- Mechanical Filtration Unit
- Nominal Particulate Reduction, Class I

STANDARD NO. 53 – HEALTH EFFECTS

- Mechanical Filtration Unit
- Cyst Reduction
- Asbestos

STANDARD NO. 401 – Emerging Compounds/Incidental Contaminants

- Microplastics

* The term “bacteriostatic” indicates that the system limits the passage or growth of bacteria that may already exist in the incoming water. It does not mean that water leaving the system is safer to drink than water entering the system.



*Filter system certified by IAPMO R&T against NSF 42, 53 and 401; against NSF 372 for lead free product. Certified against CSA B483.1.

Refer to User Guide for operation and maintenance.



**Zip Water
(Aust)**

67 - 77 Allingham Street, Condell Park NSW 2200
Postal: Locked Bag 80, Bankstown 1885
Australia
Tel (+612) 9796 3100
Free call 1800 947 827 (1800 ZIP TAP)
www.zipwater.com

**Zip Water
(UK)**

Trafalgar House, Rash's Green,
Dereham, Norfolk, NR19 1JG
0345 6 005 005
sales@zipindustries.co.uk
specify.zipwater.co.uk

**Zip Water
(NA)**

9399 West Higgins Road, Suite 1100
Rosemont, IL 60018
Free call 1-833-233-2358
www.na.zipwater.com



As Zip policy is one of continuous product improvement, changes to specifications may be made without prior notice. Images in this booklet have been modified and may not be true representations of the finished goods.

The terms "Zip" and "HydroTap" are registered trade marks of Zip Heaters (Aust) Pty Ltd.

Manufactured by Paragon Water Systems.